TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1278)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.24°W., 20 lks. dist.
A Fir 12" dia., bears N.23°W., 19 lks. dist.

Correspondance from International Paper Co., Long-Bell Division, S.D. Waite, Engineer to James Byron, Co. Surveyor, dated Sept. 28, 1966 (in C.S. File 54/30):
"Please refer to your letter of Sept. 14 requesting information about the ¼ corner to secs. 23 and 26. I can not find any record of who set the pipe. It might have been set by Clarence Doane and W.M. Robertson of Gardiner Lumber Company before it was acquired by Long-Bell. The Long-Bell crew ran a line between said pipe and a pipe marked $\frac{22\ 23}{27\ 26}$, August 7, 1950, but did not record any information about bearing trees."

Survey by Richard J. Hintz, LS #497 - For: International Paper Co.; Menasha Corporation; U.S. Forest Service - Nov. 1980 - M 84-24 A&B

Set 1¼" I.P. with stamped brass cap, from which
12" Alder bears N.7°00'W., 7.9 ft., scribed.
12" Fir bears S.34°00'W., 5.9 ft., scribed.
I made a thorough search for the iron pipe and brass cap as shown being found in C.S. 51/333 and C.S. 54/30, but its position was in the head of a draw which has now slid away to bed rock.