

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 540600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1283)

Set ¼ sec. post, from which
 An Alder 12" dia., bears N.8°E., 32 lks. dist.
 An Alder 12" dia., bears S.30°E., 32 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper Co. - March 1980 - M 79-30 and C.S. File 58/140

Set 2" I.P. with stamped brass cap, from which
 18" Spruce bears N.35°30'E., 31.3 ft., scribed.
 12" Spruce bears S.72°00'W., 42.5 ft., scribed.

Clyde Mulkins, surveyed for: Port Blakely Tree Farms; Scott Timber Co.; Menasha Corp. July 1997 - M 127-39

Found -
 2½" brass cap from which:
 32" Spruce, with a healed face bears N.36°E., 31.3 ft.
 22" Spruce, with a healed face bears S.69°W., 42.5 ft.
 (rec. S.72°W)

New Accessories -
 13" Spruce, bears N.23°W., 22.0 ft. scribed "¼ S2 BT"
 25" Spruce, bears S.22°W., 80.9 ft. scribed "¼ S11 BT"
Note - The corner falls approx. 100' north of a ridge road.