

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 600400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1271)

-----  
Set post cor. of secs. 13, 14, 23 and 24, from which  
A Spruce 36" dia., bears S.71°E., 80 lks. dist.  
A Fir 12" dia., bears N.11°E., 28 lks. dist.  
A Crab, 3" dia., bears N.81°W., 30 lks. dist.  
Tree omitted SW.

Survey by Richard J. Hintz - For: Champion International and International Paper Co. - March 1980 - M 79-30 and C.S. Fle 58/140

-----  
Set 2" I.P. with stamped brass cap from which  
36" Fir bears N.87°45'E., 162.9 ft., scribed. Scribed BT overhangs Franz Creek.  
52" Spruce bears S.58°00'E., 257.2 ft. to 50d nail in the face.

Survey by Richard J. Hintz - For: International Paper Co. - Dec. 1991 - M 114-22

-----  
Previous corner was incorrectly set in 1980. The brass cap set in 1980 was pulled up and moved to its present location. BTs recalculated:  
36" Fir bears N.87 3/4°E., 175.3 ft., scribed.  
52" Spruce bears S.59½°E., 267.9 ft. to a 50d nail in face, scribed.  
No other references within limits in secs. 14 and 23.  
The position for this corner per M 79-30 was East, 12.52 ft.

Fd. OK - C. Mulkins - March 24, 1995 - 1996-0014 A&B  
Fd per rec. R Beauduy - 8/2019 - M176-4A&D