

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1272)

Set ¼ sec. post, from which
An Alder 12" dia., bears N.9°W., 88 lks. dist.
A Cedar 8" dia., bears N.3½°E., 100 lks. dist.

Survey by Richard J. Hintz - For: International Paper and Champion International - March 1980 - M 79-30 and C.S. File 58/140

Set 2" I.P. with stamped brass cap, from which
16" Hemlock bears N.63°00'E., 20.1 ft., scribed.
16" Alder bears S.35°30'W., 10.8 ft., scribed.

Survey by Richard J. Hintz - For: International Paper - Dec. 1991 - M 114-22

Previous corner was incorrectly set in 1980. The brass cap set in 1980 was pulled up and moved to its present position. BTs recalculated:
16" Hemlock bears N.69½°E., 25.9 ft., scribed.
14" Alder bears N.3 3/4°W., 17.8 ft., scribed.
The position for this corner per M 79-30 was East, 6.26 ft.

Jerry Estabrook - For: Rayonier - 7/2019 - M176-3

Found - A 2" iron pipe with brass cap marked "T21S R12W ¼ S13 S14 PLS497 1979", per M114-22.
An 18" Hemlock stump bears N.69°10'E., 25.9'.
New BTs- A 10" Fir, face scribed "E¼ S14 BT" with X-chop and tag bears S.20°W 9.9' to a spike at side center.
A 9" Fir, face scribed "E¼ S14 BT with X-chop and tag bears N.68°W., 2.5' to a spike at side center.

LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS
N: 43°44'51.6" W: 124°05'05.7"