

PRIMARY CORNER DESCRIPTION Sec. Cor. for 11, 12, 13 and 14

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1272)

-----  
Cor. to secs. 11, 12, 13 and 14, Set post, from which  
A Fir 24" dia., bears N.12½°W., 118 lks. dist.  
A Fir 12' dia., bears N.4°E., 22 lks. dist.  
A Fir 30" dia., bears S.15°E., 36 lks. dist.  
A Fir 24" dia., bears S.17°W., 40 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper - March 1980 - M 79-30 and C.S. File 58/140

-----  
Found 3 original BTs (stumps)  
Set 2" I.P. with stamped brass cap, from which  
14" Fir bears N.27°30'E., 49.3 ft., scribed.  
16" Fir bears S.34°45'E., 13.7 ft., scribed.  
52" Fir bears S.15°00'E., 23.8 ft. Orig. BT.  
48" Fir stump bears S.17°00'W., 26.4 ft. Orig. BT.  
16" Fir bears N.66°00'W., 9.6 ft., scribed.  
50" Fir stump bears N.16°45'W., 73.0 ft. Orig. BT. (Rec. N.12°30'W., 77.9 ft.)  
14" Fir bears S.51°30'W., 27.0 ft.

Jerry Estabrook - For: Rayonier - 7/2019 - M176-3

-----  
Found - A 2" iron pipe with 2½" brass cap marked "T21S R12W 11 12 13 14 PLS497 1979", per M79-30.  
A 27" Fir stump with healed face bears N.27°30'E., 49.3'.  
A 22" Fir stump with healed face bears S.34°45'E., 13.7'.  
An original 52" fir stump bears S.15°E., 23.8'.  
An original 48" fir stump bears S.17°W., 26.4'.  
A 26" Fir, with healed face bears S.51°30'W., 27.0'  
A 21" Fir stump with healed face bears N.66°W., 9.6'.  
An original 50" fir stump bears N.16°45'W., 73.0' (N.16°45'W.) CS 58/140-3.  
New BT - An 11" fir, face scribed "SE S11 BT" with X-chop and tag bears N.22°W., 8.0' to a spike at side center.  
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS  
N: 43°45'16.8" W: 124°05'06.4"