

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1273)

Set ¼ sec. post, from which
A Fir 24" dia., bears S.66½°W., 38 lks. dist.
A Fir 18" dia., bears N.25°E., 44 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper - March 1980 - M 79-30 and C.S. File 58/140

Set 2" I.P. with stamped brass cap (offset 3.0 ft. South), from which

14" Fir bears North 2.9 ft., scribed.
16" Fir bears S.44°00'W., 14.9 ft., scribed.

Note - This corner was not accepted by Mulkins, as he found original bearing trees.

Clyde Mulkins, surveyed for: Port Blakely Tree Farms; Scott Timber Co.; Menasha Corp. July 1997 - M 127-39

Set - 5/8" x 36" rebar with a 2" alum. cap as a witness corner (true corner position bears South 1.0 ft.) from which:

Found -
34" D.Fir stump - opened up and found full original scribes, bears N.21°E., 44 lks. (orig. BT)
26" D.Fir, with partial original scribes, bears S.68°W., 38 lks. (orig. BT)

New Accessories -
27" D.Fir, bears N.67°W., 24.9 ft. scribed "WC BT"
14" D.Fir, bears S.4°E., 1.7 ft. scribed "WC BT"
17" D.Fir, bears S.54°E., 19.4 ft. scribed "WC BT"
22" D.Fir, bears N.50°E., 17.3 ft. scribed "WC BT"

Note - 2" Brass cap set from Hintz's survey M 79-30, bears N.46°35'E., 32.34 ft. from witness corner.