

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1268)

Set ¼ sec. post, from which
A Maple 18" dia., bears N.40°W., 6 lks. dist.
A Fir 40" dia., bears S.80°W., 32 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1235)

I go to the ¼ sec. cor. bet. secs. 25 and 36, T21S R12W., which is a post, 4" sq., badly decayed, marked ¼ S on N. face, from which
A Maple 18" dia., bears N.40°W., 6 lks. dist. mkd. ¼ S BT
A Fir 40" dia., bears S.80°W., 32 lks. dist. mkd. ¼ S BT.

Survey by Richard J. Hintz, LS #497 - For: International Paper Co.; Menasha Corporation; U.S. Forest Service - Nov. 1980 - M 84-24 A&B

Set 2" alum. pipe with stamped alum. cap, from which
10" Fir bears N.10°30'E., 5.8 ft., scribed.
6" Fir bears S.43°45'E., 5.7 ft., scribed.

Fd. Alum. Pipe & BTs by T. Hostetter 2/2019 - M175-35