

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1271-72)

Set ¼ sec. post, from which
 An Alder 18" dia., bears S.77°E., 8 lks. dist.
 An Alder 18" dia., bears N.69°W., 8 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper Co. - March 1980 - M 79-30 and C.S. File 58/140

Set 2" I.P. with stamped brass cap, from which
 22" Fir bears N.25°00'E., 13.4 ft., scribed.
 18" Fir bears S.66°45'W., 42.5 ft., scribed.
Corner falls in cat road.

Survey by Richard J. Hintz - For: International Paper Co. - Dec. 1991 - M 114-22

Previous corner was incorrectly set in 1980. The brass cap set in 1980 was pulled up and moved to its present position. BTs recalculated:
 24" Fir bears N.45½°E., 17.5 ft., scribed.
 18" Fir bears S.63°W., 36.8 ft., scribed.
The position for this corner per M 79-30 was East 6.25 ft.