

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 3 Page(s) 1273)

-----  
Set ¼ sec. post, from which  
A Fir 10" dia., bears North 53 lks. dist.  
A Fir 36" dia., bears S.40°E., 57 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper - March 1980 - C.S. File 58/140 and M 79-30

-----  
Set 2" I.P. stamped with brass cap, from which  
12" Fir bears N.33°45'E., 10.1 ft., scribed.  
8" Alder bears S.22°15'E., 17.6 ft., scribed.

Jerry Estabrook - For: Rayonier - 7/2019 - M176-3

-----  
Found - A 2" iron pipe with 2½" brass cap marked "T21S R12W ¼ 12 13 PLS497 1979" per M79-30.  
A 16" Fir stump with healed face and tag bears N.33°45'E., 10.1'.  
A rotten alder stump with tag bears S.22°15'E., 17.6'.  
New BTs- A 16" alder, bark scribed "N¼ S13 BT with X-chop and tag bears S.21°W., 17.25' to a spike at side center.  
A 17" alder, bark scribed "S¼ S12 BT" with X-chop and tag bears N.65°W., 18.2' to a spike at side center.  
LAT. AND LONG. PER GARMIN ETREX HAND HELD GPS  
N: 43'45'16.7" W: 124'04'31.3"

Jerry Estabrook - Crew: Blue James, Jack Jarrett & Daniel Tlemissen - 4/15/2021 - C.S. 65/109-10

-----  
REFERENCED OUT  
Found - A 2" iron pipe with 2½" brass cap marked "T21S R12W ¼ 12 13 PLS497 1979" PER M79-30.  
A 16" Fir stump with healed face and tag bears N.33°45'E., 10.1'.  
A Rotten Alder stump with tag bears S.22°15'E., 17.6'.  
A 16" Alder, bark scribed "N¼ S13 BT" with X-chop and tag bears S.21°W., 17.25' to a spike at side center.  
A 17" Alder, bark scribed "S¼ S12 BT" with X-chop and tag bears N.65°W., 18.2' to a spike at side center. continued next page

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Note - In order to protect the corner from logging activity in the area. The record monument was pulled out and a 5/8" X 30" iron rod with plastic cap marked "ESTABROOK LS2703" was set in place 1.5' +/- below the surface of the ground. Record monument will be replaced after logging activity finished.

New reference point -  
A spike in cedar stump bears S.86°E., 35.88'.

Locations & Comments -  
Lat. and Long. per GARMIN ETREX hand held GPS  
N: 43°45'16.7" W: 124°04'31.3"

Note - Compass Declination 18° EAST

Jerry Estabrook - Crew: Patrick Coy and Brandon Campbell -  
9/20/2022 - C.S. 65/111-9

-----  
Found - 5/8" iron rod set below the ground surface before logging activity was started in the area. Replaced the 5/8" iron rod with the monument originally found in place: A 2" iron pipe with 2½" brass cap marked "T21S R12W ¼ 12 13 PLS497 1979" per M79-30.

BTs - A 16" fir stump with healed face and tag bears N.33°45'E., 10.1'.  
A rotten Alder stump with tag bears S.22°15'E., 17.6'.  
A 16" Alder stump, bark scribed "N¼ S13 BT" with x-chop and tag bears S.21°W., 17.25' to a spike at side center.  
A 17" Alder stump, bark scribed "S¼ S12 BT" with x-chop and tag bears N.65°W., 18.2' to a spike at side center.

B0 - A spike in cedar stump bears S.86°E., 35.88'.

New - A steel post bears East 2.0'.  
A steel post bears West 2.0'.  
An aluminum post bears south 0.5'.

Locations & Comments: Lat. and Long. per GARMIN ETREX hand held GPS N: 43°45'16.7" W: 124°04'31.3"  
Compass Declination 18' East