

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1149)

1/4 sec. cor. is in a creek.

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - Feb/June 1971 - C.S. File 56/5-4 & M 42-27

WITNESS CORNER to 1/4 corner. This corner set from survey and lies about 6 ft. South of driveway. Wit. Cor. 250.24 ft. North of 1/4 corner.

Set Brass cap at cor. mkd: County Surveyors Office
R T 21 S R
12 S 36 | 1/4 11
W W
1971

New Accessories:

17" Maple N.82°E., 67.0 ft. scribed "W.C. CS BT"

5/8" Iron rod N.78½°W., 68.5 ft.

5/8" Iron rod S.89°W., 34.7 ft.

Douglas County Surveyors Office - Lenora Ladig; Jim Cook; Karen Cheney, crew - May 24, 1976 - C.S. File 59/15-6

Found - 1971 DCSO brass cap properly marked.
A 17" Maple bears N.82°E., 67.0 ft. Tree is alive with visible scribing "WC CS BT" in double blaze.
Found no trace of bearing objects. (SW one in swamp area. NW one has tree uprooted over area.)

New BT - 12" Fir bears N.5°W., 49.0 ft. scribed "WC 1/4 CS BT" in double blaze.

True corner lies in marsh.

Corner found and used in BLM resurvey by Deborah M. Stephens and Harvey E. Wofford, surveyed April 1990 thru April 1995 under group #1521. (DCSO records Vol. 51 Page(s) 19593)

Tony Hostetter - For: Rome Creek Timber - Feb. 2019 - M175-35

Found - 1971 brass cap witness corner, as described by DCSO. from which:

27" Maple, BT tag, bears; N.82°E., 67.0 ft to center

5/8" IR bears; N.78°30'W., 68.5 ft.

5/8" IR, bent, bears; S.89°W., 34.7 ft.