

PRIMARY CORNER DESCRIPTION Sec. cor. for 24 & 25; 19 & 30, T21-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1150)

Set post, cor. of secs. 24, 25, 19 and 30, from which
A Vinemaple 2" dia., bears N.40°E., 10 lks. dist.
An Elder 4" dia., bears S.59°E., 19 lks. dist.
A Maple 12" dia., bears N.2°W., 415 lks. dist.
No tree near SW.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1230 and 1230-31)

Sec. cor. having been destroyed, also the bearing trees, to wit, a Vine Maple 2" dia., and an Elder 4". There is a Maple answering the description, but no marks can be found on the same.
Set a sandstone 15x8x6 ins., 10" in the ground, for cor. to secs. 24, 25, 19 and 30, marked with 2 notches on S. and 4 notches on N. edges, from which
A W.Fir 6" dia., bears S.61½°W., 12 lks. dist. mkd. T21S R12W S25 BT.
A Fir 12" dia., bears S.51°E., 25 lks. dist. mkd. T21S R11W S30 BT.
A Maple 15" dia., bears N.2°W., 415 lks. dist. mkd. T21S R12W S24 BT.
A large cliff, 10 ft. high, bears N.45°E., 2 lks. dist. mkd. with a cross and B T.

Survey by Richard J. Hintz - For: International Paper Co. - Sept. 1976 - M 62-1

Set 5/8" Iron rod, from which
A 34" Cedar bears N.71°E., 36.7 ft., scribed.
A 26" Hemlock bears S.82°E., 23.6 ft., scribed.
An 18" Hemlock bears S.5°E., 22.7 ft., scribed.
A 16" Cedar bears N.58°W., 58.1 ft., scribed.
Corner is on top of ridge which bears NW and SE.

Fd. OK, Nov. 1990 - M 111-9