

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; and 19 of T21-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1150)

Set ¼ sec. post, from which
A Spruce 36" dia., bears S.9°E., 20 lks. dist.
A Spruce 10" dia., bears S.46°W., 40 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 3 Page(s) 1230)

The ¼ sec. cor. bet. secs. 19 and 24, which is a post, 4" sq., marked ¼ S. on W. face, (I think, set lately by the Co. Surveyor), from which
A Spruce 10" dia., bears S.46°W., 40 lks. mkd. ¼ S BT.
A Hemlock 36" dia., bears S.9°E., 20 lks. dist., marks have been cut out lately. (Called erroneously a Spruce in the field notes of former survey)

Survey by Richard J. Hintz - For: Robert Cowan - April 1975 -C.S. File 58/47-2

Found - Orig. BT, 30" Spruce, bears S.46°W., 26.4 ft.
1" I.P., bears S.67°55'W., 12.07 ft.
Set 1" I.P./B.C. (?)

Survey by Clyde F. Mulkins - For: I.P. Timberlands - Jan. 18, 1994 - M 118-62

Found - 1" I.P. at ¼ corner.
40" GLO Spruce stump, bears S.46°W., 26.4 ft. (slope dist.)
36" 1891 GLO Hemlock, uproot remains, (1857 GLO 36" Spruce) bears S.9°E., 13.2 ft. (slope dist.)
38" Spruce stump bears S.5°E., approx. 15 ft. Do. Co. tag.
Fd. Unrecorded Stuntzner BTs:
16" Alder bears N.14°W., 35.8 ft., bark scribed ¼ S24 BT.
38" Cedar bears S.17°W., 26.0 ft. "X" chopped into it. (tag reads 34' at 64%)
35" Spruce bears S.49°E., 10.9 ft. "X" chopped into it. (tag reads N.57½°W., 11')
19" Alder bears N.28°E., 31.7 ft. scribed ¼ S19 BT.

Fd. Ok by Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 4/18/2002 - C.S. File 66/32-32