

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T21-11

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1151)

-----  
Set post cor. of secs. 13, 18, 19 and 24, from which  
A Hemlock 10" dia., bears S.83°E., 47 lks. dist.  
A Spruce 36" dia., bears N.62°E., 42 lks. dist.  
A Hemlock 8" dia., bears N.86°W., 77 lks. dist.  
A Vine Maple 5" dia., bears S.45°W., 16 lks. dist.

F.C. Frear - Wit: N.E. Richardson; James Wolford - C.S. File 16/55 - Oct. 20, 1940 (I question this date?)

-----  
Drove 2" x 5 ft. pipe for corner, from which  
7" Fir bears S.70 3/4°E., 7.4 ft.  
12" Fir bears S.12½°E., 8.3 ft.  
8" Fir bears N.79½°W., 18.2 ft.  
10" Fir bears N.44°E., 21.8 ft.

Frank Cain - Harry Henderson, H.L. Eppstein - Jan. 25, 1929 -C.S. File 16/55 (I question this date?)

-----  
There was an Iron pipe 2" x 5 ft. driven in ground for this corner by previous surveyor, the old bearing trees gone but remains of stump check with field notes, but burned so bad, no scribe marks visible. Did not mark new tree on account of being too far off.

Survey by Harry Hugill - For: Walter Pyritz - Jan. 15, 1949 - C.S. File 40/169

-----  
At sec. cor., which point I found to be marked by an I.P. with bearing trees as called for plainly evident.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy and crew - Nov. 25, 1964 - C.S. File 53/66-56

-----  
Found - 2" Iron pipe mentioned by Frank Cain. Pipe extends approx. 12" above ground.  
No trace of any original bearing trees.  
New BTs -16" D.Fir S.8°W., 8.4 ft. mkd. T21S R12W S24 CS BT.  
14" D.Fir S.60°E., 24.7 ft. mkd. T21S R11W S19 CSBT  
13" D.Fir N.77°E., 27.2 ft. mkd. T21S R11W S18 CSBT  
No suitable trees near in section 13.  
DID NOT SET BRASS CAP.  
Corner is approx. 500 ft. W. of Smith River Road.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. cor. for 13 & 24, 18 & 19, T21-11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - James Byron, Co. Surveyor -  
John M. Powell and crew - April 1, 1970 - C.S. File 54/110

-----  
Found - 2" Iron pipe at corner, 12" above ground.  
16" now 16" D.Fir S.8°W., 8.4 ft., shows pitched  
over scribing.  
14" now 14" D.Fir S.60°E., 24.7 ft., shows pitched  
over scribing.  
13" now 13" D.Fir N.77°E., 27.2 ft., shows pitched  
over scribing.  
New BT - 12" Hemlock N.67°W., 26.4 ft. scribed T21S R12W S13  
CS BT.

Douglas County Surveyors Office - L.E. Monrean, Deputy - K.  
Reed; P. Earle; S. Flause; F. Silagy, crew - Nov. 15, 1978 -  
C.S. File 60/17-25

-----  
Found - An I.P. 2" dia., 17" high set by Frear in 1940.  
A 7" now 8" Fir, is tipped out, bears S.70 3/4°E.,  
7.4 ft. Tree partially rotted. scribing visible  
"19 BT".  
An 8" Fir now a 10 ft. high stump bears N.49½°W.,  
18.2 ft. Tree partially rotted, has healed over  
blaze.  
A Fir 10" now 12", bears N.44°E., 21.8 ft. Has  
healed blaze.  
A 16" now 21" D.Fir, bears S.8°W., 8.4 ft. Has well  
healed blaze.  
A 14" now 18" D.Fir, bears S.60°E., 24.7 ft. Has  
well healed blaze.  
A 13" now 18" D.Fir bears N.72½°E., (Rec. N.77°E.)  
26.6 ft. (Rec. 27.2 ft.)  
A 12" now 14" Hemlock bears N.67°W., 26.4 ft. Tree  
has partially healed blaze.  
No new monument or accessories set.

Survey by Robert Ward, Jr. - For: International Paper Co. -  
Jan. 6, 1988 - M 105-64

-----  
Found - 2" Iron pipe extending 16" out of ground.  
16" Hemlock bears N.68°W., 27.0 ft. with healed face  
24" Fir bears S.6½°W., 8.4 ft. with healed face.  
20" Fir stump bears S.62 3/4°E., 24.6 ft. with  
healed face.  
20" Fir stump N.72½°E., 26.8 ft. with healed  
face.  
Replaced 2" iron pipe with 3/4" alum. cap mkd. LS 1091.

(Cont. Next Page)

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24; 18 & 19, T21-11

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Clyde F. Mulkins, for I.P. Timberlands, Jan 18 1994, M118-62

-----

Found - 3¼" Alum cap with 3/4" x 30" Alum rod  
19" Hemlock with a healed face, bears N.68°W., 27'  
20" DF stump with a healed face, bears N.72½°E.,  
26.8 ft.  
27" DF with a healed face, bears S.6½°W., 8.4'  
New BT - 7" W. Fir I scribe "S13 T21S R12W BT", bears N.1°W.,  
35 ft.

Fd. Ok - Clyde Mulkins - Mar. 1995 - 1996-0014 A&B

Fd. OK - Clyde Mulkins - Sep. 1996 - M 124-16

Fd. OK - Troy Rambo - May 2010 - M160-70