

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 13; & 18, T21-11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1152)

Set ¼ sec. post, from which
A Fir 48" dia., bears West, 2 lks. dist.
A Hemlock 24" dia., bears S.30°E., 42 lks. dist.

Harry Hugill, Surveyor - Jan. 15, 1949 - C.S. File 40/169

Set a 1¼" Iron pipe, computed by proportional measurement.
12" Alder bears N.21°W., 6.2 ft.
14" Alder bears S.89°E., 14.0 ft.

Douglas Co. Surveyors Office - James Byron, Deputy - John M. Powell and crew - April 1, 1970 - C.S. File 54/110

This corner set from survey as shown, ¼ cor. prorated.
Set Brass cap at ¼ cor. mkd. County Surveyors Office
R T 21 S R
12W S13 S 18 11W
1970
New BTs -38" D.Fir N.80°W., 62.2 ft. scribed ¼ S13 CS BT.
12" Spruce S.82°E., 29.3 ft. scribed ¼ S18 CS BT.
Also found 2" I.P., S.3°W., 48.22 ft. from ¼ corner.
Creek bears West, 25.0 ft.

Fd. OK, Jan. 1988 by R. Ward - M 105-64

Survey by Clyde Mulkins - For: I.P. Timberlands - Jan. 18, 1994 - M 118-62

Found - 2½" County Brass cap
39" DF Stump with healed face, bears N.80½°W., 61.7 ft.
22" Spruce with healed face, bears S.82°E., 29.3' (record S.83 3/4°E., 29.5 ft.)
New BTs- 21" Alder I scribe "1/4 S18 BT", bears N.41°E., 8.4 ft.
18" Spruce I scribe "1/4 S18 BT", bears S.47°E., 35.8 ft.

Fd. OK - Clyde Mulkins - Mar. 1995 - 1996-0014 A&B
Fd. OK - Clyde Mulkins - Sep. 1996 - M 124-16