

sTOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 700640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 1; and 6 of T21-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCS0 records Vol. 3 Page(s) 1153)

-----  
Set ¼ sec. post, from which  
A Fir 15" dia., bears N.67°W., 33 lks. dist.  
A Fir 10" dia., bears S.46½°E., 20 lks. dist.

Survey by Richard J. Hintz - For: Champion International and International Paper - March 1980 - C.S. File 58/140 and M 79-30

-----  
Set stamped 2' I.P. with brass cap, from which  
12" Fir bears S.31°30'E., 45.2 ft. scribed.  
10" Fir bears N.25°00'W., 11.0 ft. scribed.

Survey by John C. Bentley - For I.P. Timberlands Operating Co., Ltd. - Feb. 1995 M121-68

-----  
Found - 2½" brass cap on a 2½" iron pipe (C.S. 58/140 N)  
15" D.Fir, N.24°W., 11.0 ft. Healed blaze. (rec. N.25°W.)  
Fir windfall, S.31°E., 48.5 ft. (rec. S.31°30'E., 45.2 ft.)  
New BTs - 12" Hemlock, N.61°E., 11.7 ft. scribed "¼ S6 BT"  
14" D.Fir, S.26°E., 27.9 ft. scribed "¼ S6 BT"  
16" D.Fir, S.62°W., 11.7 ft. scribed "¼ S1 BT"  
Fence post 1 ft. north of corner.

Found OK by B. Bacon, Oct. 2002 - M141-23

Stephen Stys - For: Rayonier - 7/2023 - M182-51

-----  
Found - A 2½" brass cap marked, ¼, S1 S6, PLS 497 1979, on 2" iron pipe as set per map file m79-30. Set fiberglass rod alongside.  
A 20 hemlock stump 3.5' tall with no visible marks bears N.59°E., 11.7' (N.61°E., 11.8' per map file M141-23).  
A 19" Fir stump 4.5' tall with healed face and tag bears S.27°E., 27.9'  
An 18" Fir stump 6' long laid over bears S.61°W., 11.8'.  
A 16" Fir stump 5' tall with healed face and tag bears N.23°W., 11.1'.  
LAT. and LONG. Per GARMIN ETREX hand held GPS:  
N:43°46'33.5" W:124°03'55.0"