

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1154)

Set post corner of Tps. 20 and 21 S. of Ranges 11 and 12 W., from which

- A Fir 12" dia., bears N.8½°W., 48 lks. dist.
- A Fir 15" dia., bears N.5½°E., 43 lks. dist.
- A Fir 15" dia., bears S.63°E., 17 lks. dist.
- A Fir 15" dia., bears S.85°W., 62 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 118)

Intersect West bdy. 295 lks. S. of cor. to Tps. 20 & 21 S., Rs. 11 and 12 W., which is a decayed post, 4" sq. mkd. T20S S31 on NE.; R11W S6 on SE.; T21S S1 on SW.; R12W S36 on NW. faces, with 6 notches on each edge; from which

- A Fir 15" dia., bears N.5½°E., 43 lks. dist. mkd. T20S R11W S31 BT.
- A Fir 15" dia., bears S.63°E., 17 lks. dist. mkd. T21S R11W S6 BT.
- A Fir 15" dia., bears S.85°W., 62 lks. dist. mkd. T21S R12W S1 BT.
- A Fir 12" dia., bears N.8½°W., 48 lks. dist. mkd. T20S R12W S36 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, E. West, crew - March 1967 - C.S. File 54/1-34

Found - Orig. 15" now 30" shattered Fir stump, N.5½°E., 28.4 ft. with "T20S 11W 31 BT" scribe revealed.
Orig. 15" now 30" Fir, 20 ft. high snag, S.85°W., 40.9 ft., shows scar.
Orig. 12" now 18" Fir, badly decayed stump with fragmentary reverse scribe marks, N.8½°W., 31.7 ft.
Unrecorded 40" Fir stump bears N.48°E., 40.1 ft. mkd. "S31 BT".
New BT - 24" Hemlock N.15½°E., 30.1 ft. mkd. T20S R11W S31 CS BT.

No other trees close.
This corner lies on moderate SE slope approx. 100 ft. S. of top of ridge. This area logged recently.

Fd. OK, March 1980 by R. Hintz - M 79-30

(Cont. Next Page)

TOWNSHIP 21 RANGE 12 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp. cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by John C. Bentley - For: I.P. Timberlands Operating Co., Ltd. - Feb. 1995 - M 121-68

Found 2½" aluminum pipe (set by Durham in 1964) Menasha records.

BTs per C.S. 54/1 -

- 30" Fir snag, S.88°W., 41.6 ft. (rec. S85°W., 40.9 ft.)
- 22" Hemlock stump, N.15°E. 29.8 ft. (rec. N.15½'E. 30.1')
- 38" Fir stump, N.48°W., 42.2 ft. very rotten (rec. 40.1 ft.)

Rotten Fir stump, N.5°E., 30.7 ft. scribing visible (rec. N.5½°E., 28.4 ft.)

New BTs -

- 9" D.Fir, N.39°E., 16.5 ft. scribed "S31 BT"
- 11" Alder, S.19°E., 20.9 ft. bark scribed "S31 BT"
- 8" Alder, S.61°W., 21.0 ft. bark scribed "T21S R12W S1 BT"
- 14" Alder, N.14°W., 10.1 ft. bark scribed "T20S R12W S36 BT".