

TOWNSHIP 21 RANGE 13 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1261) and (Vol. 1 Page 5)

Witness post West 25.17 chs. from true cor. of secs. 25, 30, 31 and 36. Deposited a soft sandstone 4x6 ins. No means of making better monument, land all sandy and wet; no timber.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17190)

Point for the cor. of secs. 25, 30, 31 and 36, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28" long, 2½" dia., 22" in the ground, in concrete, with alum. cap mkd:

T 21 S
R 13 W R 12 W
S 25 S 30
S 36 S 31
1981

No suitable trees available within limits.
Set a steel fence post alongside aluminum post.