

TOWNSHIP 21 RANGE 13 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T21-12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1261)

Cor. of secs. 24, 25, 19 and 30, deposited ½ pint of charcoal and burnt sticks. Raised mound with trench as per instructions.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17191)

Point for the cor. of secs. 19, 24, 25 and 30, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28" long, 2½" dia., 24" in the ground, in concrete, with alum. cap mkd:

T 21 S
R 13 W R 12 W
S 24 S 19
S 25 S 30
1981

No suitable trees available within limits.
Set a steel fence post alongside aluminum post.