

TOWNSHIP 21 RANGE 13 POINT IDENTIFIER # 700340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 24; & 19, T21-12

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by Harvey Gordon Deputy Surveyor, under Contract #69 dated Feb. 2, 1857 (DCSO records Vol. 3 Page(s) 1261)

Qr. sec. cor. in loose sand. Set witness post on top of a solid natural mound 20 ft. high, which bears S.39°E., 4.60 chs. dist. Deposited 2 boulders 4x6x8x10.

BLM resurvey by Glenn F. Goodson, Scott R. McIntyre and Scott R. McMullin, Cadastral Surveyors - Under Group #1064 - Surveyed June/Sept. 1981 - (DCSO records Vol. 44 Page(s) 17191)

Point for the ¼ sec. cor. of secs. 19 and 24, at record distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28" long, 2½" dia., 21" in the ground, in concrete, with alum. cap mkd:

T 21 S
R 13 W R 12 W
1/4
S 24 S 19
1981

No suitable trees available within limits.

Set a steel fence post alongside aluminum post.