

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 100140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 31; and 36, T22-5

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Gordon and Gardner, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1333)

Set ¼ sec. post, from which
 An Oak 24" dia., bears S.25°W., 166 lks. dist.
 An Oak 18" dia., bears S.23°E., 200 lks. dist.

Ben B. Irving, Douglas Co. Surveyor - Wit: N.E. Richardson; Loren Weber - Aug. 1940 - C.S. File 16/55 (and "old" corner book, page 18)

Location identified from one original BT.
Set a stone 8" x 8" x 12" above ground marked X ¼ S on top from which
 Fir 50" dia., bears S.24°W., 36 ft. mkd. ¼ S 36 CS BT.
 Fir 44" dia., bears N.45°E., 96 ft. mkd. ¼ S 31 CS BT.

Douglas Co. Surveyors Office - Bruce Rogers and crew - Jan. 8, 1965 - C.S. File 53/101-48

Found - 8" x 8" x 12" stone at corner mkd. X ¼ S on top.
 50" Fir now 60" S.24°W., 36 ft., bark scribing visible.
 44" Fir, now stump, N.45°E., 96 ft., bark scribing.
Set brass cap along North side stone mkd:
 County Surveyors Office
 T 22 S
 ¼ R5W S36 | S31 R4W
 1965
New BTs -11" W.Oak N.38°E., 33.1 ft. mkd. ¼ S31 CS BT.
 12" Fir N.80°W., 22.0 ft. mkd. ¼ S36 CS BT. In
 fence corner.

Fd. OK, Dec. 1983, L.Smith, M 95-74

Fd. OK, Oct. 1992, K.Hoffine, M 116-2