

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 140540

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2002, surveyed Jan/March 2002- (DCSO rec. Vol. 54 Page(s) 20822)

Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at the intersection with the E & W centerline.
Set a stainless steel post, 28" long, 2 $\frac{1}{2}$ " dia., 26" in the ground, with brass cap mkd.

T22S R4W
C $\frac{1}{4}$ S 7
2002

from which

A fir, 9" dia., bears N.28 $\frac{1}{2}$ °E., 4.4 ft., mkd. C $\frac{1}{4}$ S7 BT.
A fir, 10" dia., bears N.63 $\frac{3}{4}$ °W., 24.4 ft., mkd. C $\frac{1}{4}$ S7 BT.
Each new bearing tree has a 2 $\frac{1}{2}$ " X $\frac{1}{4}$ " magnetic nail (MAG-NAIL) driven at the base on the right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.