

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 140600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 6 and 7

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1351)

-----  
Set ¼ sec. post, from which  
A Fir 15" dia., bears S.68°W., 33 lks. dist.  
An Alder 12" dia., bears N.3°E., 150 lks. dist.

Douglas County Surveyors Office - James W. Byron, Surveyor  
Bruce Rogers, and crew - C.S. File 53/101-19 - June 2, 1965

-----  
Corner searched for, not found.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2002, surveyed Jan/March 2002- (DCSO rec. Vol. 54 Page(s) 20820)

-----  
Point for the ¼ sec. cor. of secs. 6 & 7, at proportionate dist. There is no remaining evidence of the orig. cor.  
Set a stainless steel post, 28" long, 2½" diam., 26" in the ground, with brass cap mkd.

T22S R4W  
¼      S 6  
         S 7  
2002

from which

A fir, 18" dia., bears N.68½°E., 44.1 ft., mkd. ¼ S6 BT.  
A fir, 14" dia., bears S.45½°W., 20.2 ft., mkd. ¼ S7 BT.  
Each new bearing tree has a 2½" X ¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd. BC & 2 BTs by Ronald Rice, 3/2009 - M 159-13