

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1344)

-----  
Set post cor. of secs. 29, 30, 31 and 32, from which  
A W.Oak 10" dia., bears N.88°W., 965 lks. dist.  
A W.Oak 18" dia., bears S.81½°W., 834 lks. dist.  
An Ash 10" dia., bears S.46½°W., 700 lks. dist.  
A W.Oak 12" dia., bears N.38°E., 102 lks. dist.

-----  
Daniel Baker, for Weyerhaeuser Co. Sept. 1995 - M119-73

-----  
Set 2" x 38" iron pipe with brass cap marked "T22S R4W S29 S30 S31 S32 PLS 1978 1995"

New Accessories -

- 9" Oak, S.30°E., 326.2 ft. to "W" nail, scribed "T22S R4W S32 BT"
- 11" Ash, S.56°E., 462.2 ft. to "W" nail, scribed "T22S R4W S32 BT"
- 8" Ash, S.22°W., 272.1 ft. to "W" nail, scribed "T22S R4W S31 BT"
- 11" Ash, N.82°W., 512.8 ft. to "W" nail, scribed "T22S R4W S30 BT"

Fd. Ok, Mar. 1997 by K. Hoffine - M 124-47  
Fd. OK, Oct. 1998 by D. Edwards - M 130-65  
Fd. Ok, May 2005 by K. Hoffine - M 148-9A&B  
Fd. BC & 4 BTs by C Sweeden, 8/2017 - M173-64