

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias <u>039040</u>	Description <u>S SE Cor. McDonald DLC #39</u>
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1346)

Set post cor. of secs. 19, 20, 29 and 30, from which

- A Fir 12" dia., bears S.40°W., 86 lks. dist.
- A Fir 18" dia., bears N.73°W., 48 lks. dist.
- A Fir 18" dia., bears N.46°E., 96 lks. dist.
- A Fir 24" dia., bears S.63°E., 100 lks. dist.

Frear, Wolford and A. Boyer - April 8, 1941 - (No record source, see C.S. File 16/55

Reset from all 3 old BTs. All in and OK, except one in sec. 20. Drove 1" x 36" Iron pipe and rock, from which I marked

- A 8" Fir N.69°E., (Note Boyer left out distance)

I re-marked all of the 3 old Fir trees.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 -Surveyed July 29/Aug. 23, 1963 - (DCSO records Vol. 32 Page(s) 13433)

The Sec. cor. determined from the remains of the original bearing trees:

- A sawed Fir stump 45" dia., bears S.63°E., 91 lks. dist. 100 lks. dist. on the slope, mkd. B on bark blaze. (Rec. distance 100 lks.)
- A Fir snag 35" dia., bears S.42°W., 86 lks. dist. mkd. 30 T22S R4W on opened blaze and BT on bark blaze. (Rec. bearing S.40°W.)
- A Fir snag 24" dia., bears N.73°W., 48 lks. dist. mkd. BT on bark blaze.

and a local bearing tree:

- A Fir snag 9" dia., bears N.60°E., 15½ lks. dist. mkd. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 16" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap

mkd: T 22 S R 4 W

S 19 | S 20

 S 30 | S 29

 1963

from which new bearing trees:

- A Fir 7" dia., bears N.22½°E., 54 lks. dist. mkd. T22S R4W S20 BT.
- A Fir 5" dia., bears S.33¼°E., 68 lks. dist. mkd. X BT.

(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 20, 29 and 30

Alias 039040 Description S SE Cor. McDonald DLC #39
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 8" dia., bears S.77°W., 61 lks. dist. mkd. T22S R4W S30 BT.
A Fir 13" dia., bears N.21°W., 41 lks. dist. mkd. T22S R4W S19 BT.

Survey by Daniel Baker - For: Weyerhaeuser Co. - Nov. 1994 - M 119-20

Found - 2½" USBLM Brass cap dated 1963.
48" Cut Fir stump remains at 1963 record, S.63°E., 91 lks
Original BT Fir stump remains S.41 3/4°W., 55.1 ft. deadfall has scribing (1963 record S.42°W., 86 lks. - orig. BT)
24" stump remains at 1963 record N.73°W., 48 lks.
9" Fir snag 1963 record N.60°E., 15.5 ft. - scribing visible on remains which are down and out of position.
8" Fir stub, N.23°E., 36.4 ft. - scribing visible (1963 record N.22½°E., 54 lks.)
12" Fir, S.37°E., 44.9 ft. - closed face (1963 record S.33¼°E., 68 lks)
8" Fir snag, S.76 3/4°W., 40.0 ft. scribing visible (1963 record S.77°W., 61 lks)
14" Fir stub, N.20°W., 26.8 ft. - closed face (1963 record N.21°W., 41 lks)
8" Oak, N.75°W., 4.3 ft. - closed face
Unknown 3/4" iron pipe, N.20°W., 1.7 ft.

Fd. OK, Mar. 1997 by K. Hoffine - M 124-47
Fd. OK by N. Hibbs, Nov. 2000 - M132-56
Fd. Ok, May 2005 by K. Hoffine - M 148-9A&B
Fd. Ok Aug. 2006 by K. DeGroot - M146-44
Fd. Ok 10/2015 by D. Baker - M170-27