

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1350)

Set post cor. of secs. 5, 6, 7 and 8, from which
A Fir 36" dia., bears S.89½°W., 33 lks. dist.
A Fir 18" dia., bears N.51°W., 89 lks. dist.
A Fir 6" dia., bears S.82°E., 34 lks. dist.
A Laurel 10" dia., bears N.2°E., 94 lks. dist.

Fd. and used in GL0 survey by Wm. P. Wright, under Contract #514 dated Aug. 27, 1884 (DCSO records, Vol. 4 page 1365)

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Mike Stone & Vernon "Ray" Tracy, crew - 9/1962 - C.S. 49/42-59

Found - Fir stump, now 48", S.82°E., 22.4 ft., cut open to 6" dia., and find good scribing "8".
Fir stump now 48", S.89½°W., 21.8 ft. No scars or scribing found.
Rotted remains of Fir, uproot, N.51°W., 58.7 ft. Too far gone to show scars or scribing.
No trace found of NW. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 4 W
S 6 | S 5
S 7 | S 8
1962

New BTs -10" W.Fir S.9°W., 80.8 ft. mkd. T22S R4W S7 CS BT.
12" D.Fir S.20½°E., 34.8 ft. mkd. T22S R4W S8 CS BT.
No other trees available.
Scribe 30" Fir stump N.15°E., 35.8 ft. mkd. T22S R4W S5 CS BT.

A 1/2" alum. pipe bears N.75°E., 2.0 ft. from corner.

Fd. OK, Feb. 1991 - M 111-75
Fd. OK, Sept. 1992 by D. Peel - M 115-77
Fd. OK, Dec. 1994 by Les Roberts - M 121-26

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2002, surveyed Jan/March 2002- (DCSO rec. Vol. 54 Page(s) 20819-20)

The cor. of secs. 5, 6, 7, & 8, remonumented by Godfrey, in 1962, recovered by Peel, in 1991 & 1992, and recovered by Roberts, in 1994, monumented with an iron post, 1½" diam., firmly set, projecting 12" above ground, with brass cap (properly) mkd. continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 5, 6, 7 and 8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of the original bearing trees

- A decayed fir stump, size indeterminate, bears S.82°E., 22.4 ft., with no marks visible.
- A decayed fir stump, 39" dia., bears N.88¾°W., 21.8 ft., with healed blaze. (Record S.89½°W.)

and remains of bearing trees mkd. by Godfrey

- A decayed fir stump, size indeterminate, bears N.15¼°E., 36.3 ft., with no marks visible.
- A fir stump, 24" dia., bears S.19½°E., 34.6 ft., with healed blaze.
- A fir stump, 30" dia., bears S.9°W., 80.8 ft., with healed blaze.

and new bearing trees

- A cedar, 28" dia., bears S.73½°E., 100.9 ft., mkd. T22S R4W S8 BT.
- A maple, 20" dia., bears S.15¼°W., 81.4 ft., mkd. T22S R4W S7 BT.
- A fir, 23" dia. bears N.30°W. 38.7 ft. mkd. T22S R4W S6 BT

Each new bearing tree has a 2½" X ¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center.

From this point, an aluminum pipe, ½" diam., firmly set, projecting 6" above ground, bears East, 2.0 ft.

See last page for BLM Control Data Sheet.

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 200600

PRIMARY CORNER DESCRIPTION Sec Cor for 5, 6, 7 and 8

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

5/3/2004	Control Data Sheet
Bureau of Land Management Oregon State Office Branch of Geographic Sciences Cadastral Survey Section	

Control Station	NAD 83 (CORS) Data
Station Name: 20060022S04W	Adjustment Software: TRIMBLE GEOMATICS v.1.50
EC Number:	Geoid Computations: GEOID 96 v.1.00
County: DOUGLAS	Latitude: 43° 40' 41.27033"
State: OR	Longitude: 123° 12' 24.958"
BLM District: ROSEBURG	Ellipsoid Height: 121.449 m
BLM Resource Area: SWIFTWATER	Geoid Separation: -22.924 m
Location: T22S, R04W, SEC.07	MSL Elev (NAVD 88): 277.306 m
Meridian: WILLAMETTE	NAVD88 - NGVD29: 1.115 m
Mapping References	Error Ellipse (95%)
USGS 7 1/2' QUAD: CURTIN	Semi-Major: 0.06 m
USGS 15' QUAD:	Semi-Minor: 0.042 m
Group Number: 2002	Axis Azimuth: 145
Date Occupied: 3/27/2002	Vertical: 0.206 m
Method: GPS, STATIC, CARRIER PHASE	NAD 27 Data
Receiver Type: TRIMBLE 4600	Derivation: CORPSCON v.5.11
Baseline Software: TRIMBLE GEOMATICS v.1.50	Latitude: 43° 40' 41.8352"
Vert Shift Software: VERTCON v.1.00	Longitude: 123° 12' 20.65829"

Horizontal Reference Stations Utilized
 NGS CORS Stations CAPE BLANCO CORS ARP, DODSON BUTTE CORS ARP and CORVALLIS CORS ARP

Description
 An iron post, 1 1/4 ins. diam., firmly set, projecting 12 ins. above the ground, with Douglas County Surveyors Office brass cap mkd.

T 22 S
 S 6 | S 5
 S 7 | S 8
 R 4 W
 1956

HOW TO REACH: See quad sheet listed above for directions on how to reach this corner.

Notes

- Please send updated recovery information to: Branch of Geographic Sciences, Cadastral Survey Section (OR-957.1), Bureau of Land Management, P.O. Box 2965, Portland, Oregon, 97208. (503) 808-6132
- All distances in "HOW TO REACH" description are in miles, unless otherwise noted

