

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 5 and 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1366)

-----  
Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for qr. sec. cor. marked ¼ S on W. face, from which  
A Fir 6" dia., bears S.75°W., 30 lks. dist. mkd. ¼ S BT.  
A Fir 14" dia., bears N.37½°E., 44 lks. dist. mkd. ¼ S BT

Survey by Gilbert A Gardner - For: W.A. Woodard Lumber Co. - Oct. 24, 1953 - C.S. File 41/221

-----  
Two bearing trees:  
16" D.Fir bears S.80°W., 31.0 ft.  
20" E.Cedar S.67°E., 28.0 ft.

Survey by Les Roberts, L.S. 1039 - For: Seneca Jones Timber Co. - Dec. 1994 - M 121-26

-----  
Found - 24" Fir stump, S.75°W., 19.9', (scribe vis.) 1855 BT.  
24" Fir stump, N.37°E., 29.0', (scribe vis.) 1855 BT.  
26" Fir, S.85°W., 34.5' (scribe vis), 1953 BT  
36" I.Cedar, S.70°E., 30.3' (scribe vis), 1953 BT  
Set 5/8"x30" iron pin w/yellow plastic cap stamped "ROBERTS P.L.S. 1039"