

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 240200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1345)

Set qr. sec. post, Drove charred stake, raised mound with trench as per instructions.

Daniel Baker, for Weyerhaeuser Co. Sept. 1995 - M 119-73

Set - 2" x 38" iron pipe with brass cap marked:

T22S R4W
 $\frac{1}{4}$ S 29
S 32

PLS 1978 1995

New Accessories -

- 5/8" x 30" rebar w/cap, N.20 $\frac{1}{4}$ °E., 9.6 ft.
- 5/8" x 30" rebar w/cap, S.30 $\frac{3}{4}$ °E., 6.3 ft.
- 5/8" x 30" rebar w/cap, S.55°W., 13.7 ft.
- 5/8" x 30" rebar w/cap, N.39 $\frac{1}{4}$ °W., 10.7 ft.

Note: Caps are yellow plastic, inscribed "D.W. Baker PLS 1978".

Fd. Ok, May 2005 by K. Hoffine - M 148-9A&B