

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1348)

-----  
Set ¼ sec. post, from which  
A Fir 20" dia., bears S.24°E., 15 lks. dist.  
A Fir 24" dia., bears N.20°W., 65 lks. dist.

Lester Calder by Wm. Wilt - For: WEYCO - 7-1961/5-1962 (Filed Oct. 1962 - C.S. 51/87-5 & C.S. 53/105-13\*)

-----  
GL0 survey record, 1856:  
Post, gone.  
20" Fir S.24°E., 15 lks., No trace.  
24" Fir N.20°W., 65 lks., No trace.  
Set 1" alum. pipe for cor. by single proportion method.  
Referenced by Wm. Wilt\*: (Weyerhaeuser method with disc. #2149):  
6" Fir S.51°E., 15.6 ft.  
6" Fir S.67°W., 36.1 ft.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 - Surveyed July 29/Aug. 23, 1963 - (DCSO records Vol. 32 Page(s) 13436)

-----  
The 1/4 sec. cor., reestablished and recorded by Weyerhaeuser Timber Co., at single proportionate distance, monumented with an alum. pipe, 1" dia., firmly set, protruding 6" above ground, from which  
A Fir 6" dia., bears S.49½°E., 27 lks. dist. mkd. with a plate and nail with W stamped on head. I mark this same tree "¼ S20 BT"  
A Fir 6" dia., bears S.66½°W., 55 lks. dist., mkd. with a plate and nail with W stamped on head.  
At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:  
¼  $\frac{S\ 17}{S\ 20}$   
T 22 S R 4 W  
1963  
from which a new bearing tree:  
A Fir 7" dia., bears N.63½°W., 102 lks. dist. mkd. ¼ S17 BT.  
Reset aluminum pipe alongside iron post.