

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1349)

-----  
Set ¼ sec. post, from which  
A B.Oak 10" dia., bears S.10°W., 45 lks. dist.  
A Fir 6" dia., bears N.22°W., 97 lks. dist.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 1965 - C.S. File 53/101-69

-----  
Found - Orig. 6" Fir, now rotted stump N.22°W., 64.0 ft. chopped out, found scribing "¼ S".  
¾" galv. I.P., 2 ft. West of corner, unrecorded.  
No trace of SW. tree.

Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 4 W  
¼  $\frac{S}{S}$   $\frac{8}{17}$   
1965

New BTs -18" Cedar S.19°W., 34.0 ft. mkd. ¼ S17 CS BT.  
16" D.Fir N.83°E., 42.4 ft. mkd. ¼ S8 CS BT.

Survey by Donald Peel, LS #752 - For: Weyerhaeuser Co. - Sept 1992 - M 115-77

-----  
Found - 1¼" Iron pipe with 1965 DCSO brass cap.  
26" Fir N.81¼°E., 41.1 ft., closed face.  
32" Cedar S.18½°W., 33.8 ft., closed face, BLM tag.  
16" Fir stub N.21 ¾°W., 63.9 ft., visible scribe "BT". (Orig.)  
25" Fir S.53 ¾°W., 19.3 ft., closed face. No record of this BT.

Fd. OK 3/2006 by M. Heimbürger - M150-14