

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 32 and 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1339)

Set ¼ sec. post, from which
An Ash 24" dia., bears S.7 ¾°E., 1417 lks. dist.
A W.Oak 8" dia., bears N.76°W., 752 lks. dist.

G.A. McHenry; P.D. Wolford - Sept. 1921 - No record source -
See "Old" corner renewal book 1, Page 17

Set 4" x 36" Oak post, from which
A 14" W.Oak bears N.20 ¾°W., 776.0 ft.
A 20" W.Oak bears N.22°10'E., 852.0 ft.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone & Stoffel, crew - Dec. 1964/Jan. 1965 - C.S. File 53/101-49

Found - 14" W.Oak N.20¼°W., 776.0 ft., true brg. N.21½°W.,
shows old scribing "BT".
20" W.Oak N.22°E., 852.0 ft., true brg. N.23½°E.,
now rotten stump, chopped out, found scribing.

Record bearings and distances didn't come together, so
SET ¾" iron rod at intersection of the distances.
Set Brass cap 30 ft. South, mkd. County Surveyors Office
T 22 S R 4 W
Wit. Cor. 30' N. to Corner
¼ S32 | S33
1965

Corner is 3.0 ft. N. of centerline Road #8
Bearing objects:
Guy pole 4C-32A, South, 3.3 ft.
Power pole 4C-32, N.3°E., 60.0 ft.

Fd. OK, Dec. 1994 by W. Ruppert - 1995-0019 A-C
Fd. Ok July 2005 by D Wellman - M148-20