

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1339)

Set post, cor. of secs. 28, 29, 32 and 33, from which
A W.Oak 24" dia., bears S.88½°W., 306 lks. dist.
A W.Oak 10" dia., bears N.60°W., 153 lks. dist.
A W.Oak 8" dia., bears N.45°E., 258 lks. dist.
No other tree convenient in sec. 33.

O.F. Thiel - Dec. 15, 1950 - Mrs. Vroman - Thiel's Field Book 20 Page 5

1" by 24 SW tree stand with marks. Found an old stake along fence, found the SW tree had been cut into and old marks found remarked with S32. NE tree not to be found. NW tree cut in, no marks to be found. Set an iron shaft 30" long x 3/4".

Douglas County Surveyors Office - Wm. S. Stoffel; Mike Stone Dec. 1964 - C.S. File 53/101-62

Found - 3/4" Iron bar at cor. and 3/4" Iron rod, not recorded.
24" W.Oak S.88½°W., 202 ft., found scribing "BT", now dead 32" W.Oak.
NW and NE BTs not found. No SE BT.
New BTs -16" B.Oak S.42°W., 88.0 ft. scribed T22S R4W S32 CS BT.
11" W.Oak N.31°W., 58.5 ft. mkd. T22S R4W S29 CSBT.
28" Fir N.7°E., 52.7 ft. mkd. T22S R4W S28 CSBT.
No SE Bearing tree.

Survey by Daniel Baker, for Weyerhaeuser Co. Sept. 1995 - M119-73

Found - Monument found by Douglas Co. in 1964 is missing.
21" Oak, S.43°W., 90.1 ft. - closed face.(record: S.42°W., 88.0 ft. - 1964, Douglas Co.)
17" Oak, N.33½°W., 58.7 ft. - closed face.(record: N.31°W., 58.5 ft. - 1964, Douglas Co.)
35" Fir, N.5°E., 52.9 ft. - closed face.(record: N.7°E., 52.7 ft. - 1964 Douglas Co.)
Set 2" x 38" iron pipe with brass cap at appropriate position from remaining BT evidence as noted above. Brass cap marked:
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

	T22S	R4W
	S29	S28
	S32	S33
	PLS	1978
	1995	
New BT - 9" Fir, S.61°W., 67.2 ft. to "W" nail, scribed "T22S R4W S32 BT"		

Fd. OK by D. Edwards, Oct. 1998 - M130-65