

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300240

PRIMARY CORNER DESCRIPTION 1/4 Cor. For Secs. 28 and 29

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1340)

Set post, gr. sec., from which
A Fir 8" dia., bears S.69°W., 79 lks. dist.
A Laurel 10" dia., bears N.45°E., 71 lks. dist.

Wilford N. Haines - Nov. 1962 - H-118 and H. En. 28 (Haines Field Book 118 and Haines envelope 28)

Orig. BTs:
8" Fir S.69°W., 79 lks., now 56"±, good scars.
10" Laurel N.45°E., 71 lks., gone.
Set 1" x 1" x 36" T.Iron. There is part of scribed stake and a fence cor. 1 ft. East.
Scribed: 12" Inc. Cedar N.59°E., 56.4 ft.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 1965 - C.S. File 53/101-75

Found - Haines "T" Iron, 1 ft. from fence corner.
12" Cedar N.58°E., 56.4 ft.
45" Fir, probably 8" orig. BT, S.69°W., 52.1 ft.
Opened 45" Fir, found good scribing "S".
New BT - 15" Fir S.73°W., 27.0 ft. mkd. ¼ S29 CS BT.

Fd. OK, Feb. 1991 - M 111-66

Daniel Baker, for Weyerhaeuser Co. Sept. 1995 - M119-73

Found - Wilford Haines "T" iron - H 118
29" Cedar, N.58 3/4°E., 56.5 ft. - closed face.
record: N.58°E., 56.4 ft. - H 118.
50" Fir stump, S.69½°W., 51.9 ft. - no marks.
record: S.69°W., 79 links - 1855 GLO.
22" Rotten Fir stump, S.76¼°W., 26.6 ft. - closed face. - record: S.73°W., 27.0 ft. - 1965 Doug Co.
New Accessories -
22" Chinquapin, S.3°W., 45.4 ft. to "W" nail, scribed "¼ S29 BT"
9" Fir, N.62°W., 12.7 ft. to "W" nail, scribed "¼ S29 BT"
13" Fir, N.7°W., 26.4 ft. to "W" nail, scribed "¼ S29 BT"
6 ft. metal fence post alongside.

Fd. Ok, May 2005 by K. Hoffine - M 148-9A&B