

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1340)

-
- Set post, cor. of secs. 20, 21, 28 and 29, from which
- A Fir 12" dia., bears N.88°W., 117 lks. dist.
 - A Fir 18" dia., bears S.34°W., 63 lks. dist.
 - A Fir 3" dia., bears S.56°E., 216 lks. dist.
 - A Fir 40" dia., bears N.86°E., 263 lks. dist.

O. F. Thiel - For: J.L. Lane - Feb. 8, 1947 - Thiel Field Book 3 Page 15

Old bearing trees to sec. cor. dead. SW standing.
Set a Fir stake in place of old for NE Cor. Sec. 29.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 - Surveyed July 29/Aug. 23, 1963 - (DCSO records Vol. 32 Page(s) 13425)

The Sec. cor., determined at record distance from the remains of the original bearing trees:

- A down, rotting Fir 55" dia., bears N.86°E., 263 lks. dist. mkd. with a decayed blaze, no scribing visible.
- A rotted Fir stump 15" dia., bears S.52½°E., 46 lks. dist. no marks remaining. (Rec. brg. S.56°E.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 22 S R 4 W
S 20 | S 21
S 29 | S 28
1963

from which new bearing trees:

- A Fir 15" dia., bears N.26°E., 133 lks. dist. mkd. T22S R4W S21 BT.
- A Fir 8" dia., bears S.82°E., 11 lks. mkd. T22S R4W S28 BT
- A Fir 8" dia., bears S.27°W., 29 lks. mkd. T22S R4W S29 BT
- A Fir 17" dia. bears N.54½°W., 47 lks. mkd T22S R4W S20 BT

Fd. OK, Feb. 1991 - M 111-66

Daniel Baker, for Weyerhaeuser Co. Sept. 1995 - M119-73

Found - USBLM Brass cap dated 1963.
23" Fir, N.26°E., 88.3 ft. - closed face.
(record: N.26°E., 133 links - 1963 BLM.)
15" Fir, S.80°E., 7.1 ft. - closed face.
(record: S.82°E., 11 links - 1963 BLM.) cont.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21 28 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

9" Fir snag, S.27½°W., 18.6 ft. - closed face.
(record: S.27°W., 29 links - 1963 BLM.)
27" Fir, N.54°W., 30.9 ft. - closed face.
(record: N.54½°W., 47 links - 1963 BLM.)
New Accessory - 6 ft. metal fence post, 1 foot north

Found OK by D. Baker, Mar. 2002 - M137-51

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor,
and Robert H. Browning, Surveying Tech. Group No. 2170
surveyed Aug 2007/Feb 2008 - (DCSO records Vol. 55 Pg 21806)

The cor. of secs. 20, 21, 28, and 29, monumented with an iron
post, 2½" dia., firmly set, projecting 7" above ground, with
brass cap (properly) mkd.
from which the remains of an original bearing tree
A root hole, bears N.86°E., 173.6 ft., with fallen fir
snag, size indeterminate, lying alongside, no marks
visible.
and the remains of bearing trees mkd. by Beck
A sawed fir stump, 24" dia., bears N.26°E., 87.8 ft., no
marks visible.
A sawed fir stump, 17" dia., bears S.82°E., 7.3 ft., with
a healed blaze.
A sawed fir stump, 14" dia., bears S.27°W., 20.4 ft., no
marks visible. (Record, 19.1 ft.)
A sawed fir stump, 30" dia., bears N.54½°W., 31.0 ft.,
with a healed blaze.
and new bearing trees
A fir, 3" dia., bears N.55½°E., 69.1 ft., mkd. X BT.
A fir, 3" dia., bears S.37°E., 17.5 ft., mkd. X BT.
A fir, 3" dia., bears S.26¾°W., 35.0 ft., mkd. X BT.
A fir, 4" dia. bears N.48¼°W., 4.4 ft mkd. T22S R4W S20 BT
The geographic position (NAD 1983 (CORS 96)) of the following
corners, as determined in a least squares adjusted network of
conventional survey control and GPS occupied points,
utilizing dual frequency carrier phase GPS receivers,
relative to National Spatial Reference System (NSRS)
Continuously Operating Reference Stations (CORS) "DCSO CORS
ARP" and "OBEC CONS COOP CORS ARP", is as follows.
Latitude: 43°38'05.35"N. Longitude: 123°11'13.12"W.