

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1341)

Set ¼ sec. post, from which
A Fir 40" dia., bears S.50°W., 23 lks. dist.
A Maple 6" dia., bears N.62°E., 34 lks. dist.

O.F. Theil - For: J.L. Lane - March 1, 1947 - Field Book 3 Page 21

No trace of old cor. 1.67 West fence line, old Fir tree. No marks for sure. At 1/4 cor. iron pipe 1¼" x 30", marked:
A Cedar 7" N.40°E., 7.3 ft.

Douglas Co. Surveyors Office - Milo E. Godfrey, Deputy - Clete Putnam & Vernon "Ray" Tracy, crew - Dec. 21, 1961 - C.S. File 49/42-51

Found - Old rotten Fir snag, bark gone on NE side, S.50°W., 15.2 ft.
Old stump hole with pieces of rotten Maple N.62°E., 22.4 ft., a Maple tree is now growing in SW. side of hole, no scribing.
Old 1¼" pipe with Cedar tree to NE. showing scribing in scar opened several years ago, now nearly healed over again, bears N.33°E., 2.9 ft.
Corner of old wooden fence, nearly all down, bears NW. 5.5 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T 22 S R 4 W
¼ S20 | S21
1961

The Cedar mentioned above, 17", bears N.23°E., 11.0 ft., scribing visible "¼ SRS".
New BT - 8" R.Cedar N.57°W., 21.4 ft. mkd. ¼ S20 CS BT.
Creek crossing North of corner checks call in govt. field notes.

Lester E. Calder by Robert Barta - For: Weyerhaeuser Company - Sept. 1962 (Filed Oct. 1962) - C.S. File 51/87-6 & C.S. 53/105-22*

GL0 survey record, 1855 post, gone.
Found - DCSO brass cap set by Co. Surveyor 1961.
6" Maple N.62°E., 34 lks., 12" Maple, chopped on and no scribing visible.
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

40" Fir S.50°W., 23 lks., 40" x 12 ft. Fir snag, chopped on and no scribing visible.
Referenced by Robert Barta* (Plates and "W" nails only):
14" R.Cedar N.24°E., 9.7 ft.
10" R.Cedar S.27°W., 28.0 ft.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 -Surveyed July 29/Aug. 23, 1963 - (DCS0 records Vol. 32 Page(s) 13426)

The ¼ sec. cor., perpetuated and recorded by Godfrey, monumented with an iron post 1" dia., firmly set, protruding 14" above ground, with mkd. brass cap from which the remains of the original bearing trees:

- A stump hole with Maple shoots, bears N.62°E., 34 lks. dist.
- A Fir snag 48" dia., bears S.50°W., 23 lks. dist., no marks remaining.

bearing trees mkd. by Godfrey:

- A broken Cedar stump 17" dia., bears N.22°E., 16 lks. dist. mkd. with a healed blaze.
- A Cedar 9" dia., bears N.56¼°W., 32½ lks. dist. mkd. ¼ S20 CS BT on partially healed double blaze.

and new bearing trees:

- A Cedar 10" dia., bears S.88°E., 53 lks. dist. mkd. ¼ S21 BT.
- A Cedar 9" dia., bears S.27°W., 44 lks. dist. mkd. ¼ S20 BT.

Survey by Steven P. Ness, LS #811, For: Weyerhaeuser Company - March 30, 1993 - M 116-66

Found - 2½" DCS0 brass cap on 1¼" Iron post.
16" R.Alder S.6°16'E., 7.9 ft. small healed face. (No record.)
24" W.R. Cedar S.88°21'E., 35.5 ft. healed face (Rec. S.88°E 53 lks.)
20" W.R. Cedar S.26°53'W., 28.5 ft. healed face (Rec. S.27°W., 44 lks.)
17" W.R. Cedar N.56°15'W., 20.7 ft. healed face (Rec. N.56¼°W., 32½ lks.)

Found OK by D. Baker, Mar. 2002 - M137-51

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCS0 recs Vol. 55 Page 21807-8)

The ¼ sec. cor. of secs. 20 and 21, monumented with an iron post, 1¼" dia., firmly set, projecting 15" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A root hole with maple shoots, bears N.62°E., 22.4 ft., no marks visible.

A decayed fir snag, size indeterminate, bears S.50°W., 15.2 ft., no marks visible.

and the remains of a BT mkd. by Thiel, in 1947, (Record, incorrectly attributed to Godfrey by Beck)

A decayed cedar stump, size indeterminate, bears N.22°E., 10.6 ft., with a hollow blaze, no marks visible.

and a BT mkd by Godfrey, in 1961 reported by Beck

A cedar, 22" dia., bears N.56¼°W., 21.4 ft., with a healed blaze.

and bearing trees mkd. by Beck

A cedar, 31" dia., bears S.88°E., 35.0 ft., with a healed blaze.

A cedar, 25" dia., bears S.27°W., 29.0 ft., with a healed blaze.