

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300360

PRIMARY CORNER DESCRIPTION N 1/16 betw. Secs. 20 & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 -Surveyed July 29/Aug. 23, 1963 - (DCSO records Vol. 32 Page(s) 13426-27)

Set an iron post 28" long 2½" dia., 22" in the ground with brass cap mkd:
 N 1/16
 S 20 | S21
 T 22 S R 4 W
 1963

from which
 A Fir 32" dia., bears N.34 3/4°E., 56 lks. dist. mkd. N 1/16 S21 BT.
 A Fir 15" dia., bears N.32½°W., 86 lks. dist. mkd. N 1/16 S20 BT.

From this point, an alum. pipe, 1" dia., established and recorded by Weyerhaeuser Timber Co., firmly set, protruding 6" above ground, bears N.31°W., 18 lks. dist.

WEYCO - 1958 to 1963 - C.S. 51/87-6 & C.S. File 53/105

Found - Brass cap set by Cadastral, 1963.
 Placed 1" aluminum alongside.
 ~~28" Fir N.56°E., 31.6 ft.~~
 ~~28" Fir N.07°W., 21.2 ft.~~ (Destroyed 2/64 by Weyer)
New BTs -10" Fir N.31°W., 56.1 ft. (1963 BT) added "W" nail and plate.
 32" Fir N.36°E., 34.5 ft. (1963 BT) added 1962 "W" nail and plate (2149).

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO records Vol. 55 Pg 21808)

The N 1/16 sec. cor. of secs. 20 & 21, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground (alongside of which is an aluminum pipe, 1" dia., firmly set, projecting 4" above ground), with brass cap (properly) mkd. from which the remains of bearing trees mkd. by Beck
 A fir, 48" dia., bears N.34¾°E., 37.0 ft., with a healed blaze.
 A sawed fir stump, 21" dia., bears N.32½°W., 56.8 ft., no marks visible on a partially opened blaze.
and a new bearing tree
 A fir, 14" dia., bears S.84°W., 76.1 ft. mkd. N1/16 S20 BT