

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1341)

Set post cor. of secs. 16, 17, 20 and 21, from which
A Fir 20" dia., bears S.62°E., 36 lks. dist.
A Fir 18" dia., bears N.37°E., 106 lks. dist.
A Fir 60" dia., bears N.4½°W., 145 lks. dist.
A Fir 30" dia., bears S.60°W., 84 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - N.E. Richardson; Jim Cox; Jod Jackson; Ed Toland; F.L. Tandy; J. Jespersen, Witnesses - Sept. 18, 1928 - C.S. File 22/32; (and "old" corner book, Vol. 1 Page 17)

Position identified from one OBT, S.60°W., 84 lks. Old scribe marks visible. Remains of old BT, S.62°E., 36 lks., rotted and burned but portion of old scar visible. Also old stump checks for OBT, N.4½°W., 145 lks.
Set for corner, 4" x 6" x 42" Cedar post, scribed T22S S17 on NW. face; R4W S16 on NE. face; S21 CS on SE. face; S20 on SW. face. from which
8" Fir N.61°10'E., 41 lks.
30" Fir S.71°40'E., 11 lks.
36" Fir N.29°05'W., 306 lks.
60" Fir S.58°25'W., 84 lks.

Survey by Lester B. Calder by Robert Barta - For: Weyerhaeuser Co - Sept. 1962 - C.S. File 51/87-5 & 53/105-14*

GL0 Survey, 1855:
Post, gone.
18" Fir N.37°E., 106 lks., no trace.
20" Fir S.62°E., 36 lks., Found rotted stump only.
30" Fir S.60°E., 84 lks., 54" Fir stump.
60" Fir N.4½°W., 145 lks., rotten windfall, no scribing visible.
County Survey record, 1928:
Cedar post, in place, scribing visible.
8" Fir N.61°10'E., 41 lks., 20" Fir, healed faces.
30" Fir S.71°40'E., 11 lks., 36" Fir, scribing visible.
60" Fir S.58°25'W., 84 lks., 45" Fir stump, healed basal scar.
36" Fir N.29°05'W., 300 lks., 42" Fir snag, bark scribing visible.
Referenced by Wm. L. Wilt* (plates and "W" nails only)
20" Fir N.60°E., 27.4 ft.
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

36" Fir S.85°E., 6.8 ft.
14" Fir S.21°W., 29.2 ft.
14" Fir N.62°W., 54.8 ft.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 -Surveyed July 29/Aug. 23, 1963 - (DCSO records Vol. 32 Page(s) 13427)

The Sec. cor., perpetuated by Haines, #239, with a 1" T-Iron, firmly set, protruding 8" above ground, with alum. cap mkd. "Wilford N. Haines, No. 239 Drain, Oregon" at record bearing and distance from the remains of the original bearing trees:

A stump hole, bears S.62°E., 36 lks. dist.
A sawed Fir stump 60" dia., bears S.60°W., 84 lks. dist., to face, no marks remaining. (Rec. dist. 84 lks.)
A stump hole, bears N.4½°W., 145 lks. dist.

bearing trees mkd. by the County in 1928:

A Fir 20" dia., bears N.60°E., 43 lks. dist. mkd. with a healed double blaze.
A Fir 36" dia., bears S.85°E., 12½ lks. dist. mkd. T22S R4W S21 CS BT on bark blaze.
A Fir snag 42" dia., bears N.29°W., 300 lks. dist. mkd. T22S R4W CS BT on double blaze.

and a locally mkd. tree:

A Fir 14" dia., bears S.22½°W., 44½ lks. dist. mkd. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 4 W	
S 17	S 16
S 20	S 21
1963	

from which a new bearing tree:

A Fir 14" dia., bears N.61°W., 84 lks mkd. T22S R4W S17 BT

David Wellman, May 29, 1997 - C.S. File 65/15-2

Found - 1" T-iron & 1963 BLM brass cap
60" Fir stump, S.60°W., 84 lks.
20" Fir, N.60°E., 43 lks.
36" Fir, S.85°E., 12½ lks.
14" Fir, S.22½°W., 44½ lks.

New Accessories -

12" Fir, N.71°W., 16.8 ft. to "W" nail - scribed "T22S R4W S17 BT"
29" Fir, S.89°W., 33.4 ft. to "W" nail - scribed "T22S R4W S20 BT"

Note - 6 ft. metal fence post 1 ft. north.

Cont.

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO recs Vol. 55 Pgs 21808-9)

The cor. of secs. 16, 17, 20, & 21, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground (alongside of which is an iron T-post, 1" sq., firmly set, projecting 5" above ground with brass disk mkd. WILFORD N HAINES 239 DRAIN ORE), with brass cap (properly) mkd.

from which the remains of an original bearing tree
A decayed fir stump, size indeterminate, bears S.60°W., 55.4 ft. to face, no marks visible.
and the remains of BTs mkd. by Irving, in 1928, reported by Beck

A decayed fir stump, 39" dia., bears S.85°E., 8.2 ft., no marks visible.

A decayed fir stump, size indeterminate, bears N.30¾°W., 194.3 ft., no marks visible. (Record, N.29°W., 198.0 ft.)

and the remains of a BT mkd. by Calder, in 1962, reported by Beck

A sawed fir stump, 28" dia., bears S.22½°W., 29.4 ft., with a healed blaze.

and the remains of BTs mkd. by Wellman, in 1997

A sawed fir stump, 30" dia., bears N.88°W., 34.1 ft., with scribe marks T22S R4W S20 visible on an open blaze.

A sawed fir stump, 11" dia., bears N.72¾°W., 17.5 ft., with scribe marks T22S R S17 BT visible on an open blaze.

and new bearing trees

A fir, 11" dia., bears N.75¼°E., 19.6 ft., mkd. T22S R4W S16 BT.

A fir, 12" dia., bears S.1¼°E., 21.9 ft., mkd. T22S R4W S21 BT.

A maple, 4" dia., bears N.18°W., 26.0 ft., mkd. X BT.