

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 3 Page(s) 1342)

-----  
Set ¼ sec. post, from which  
A Fir 10" dia., bears N.50°E., 29 lks. dist.  
A Fir 6" dia., bears N.84°W., 8 lks. dist.

Ben B. Irving, Deputy Co. Surveyor - Wit: N.E. Richardson; Jim Cox; Jod Jackson; Ed Toland; F.L. Tandy; J. Jespersen - Sept. 18, 1928 - C.S. File 22/32 and ("old" renewal book, Vol. 1 Pg. 17)

-----  
Position identified by OBT, 24" Fir N.50°E., 29 lks.  
Set gun barrel for corner and a 6" x 5" Yew wood post, from which  
Blazed and scribed OBT, "¼S 16 CS BT".  
Blazed and scribed 8" Fir N.80°W., 22.3 ft. "¼S 17 CS BT"

Wilford Haines - C.S. File 49/42-67(2) (Date ?) Added 7/22/2021

-----  
Found - Gun barrel in ground  
Fir 6" N.50°E., 29 lks.  
Fir 6, N.84°W., 8 lks  
Scribed- 12" yew, N.15°W., 21.0 ft.

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone & Stoffel, crew - Dec. 1964/Jan. 1965 - C.S. File 53/101-50

-----  
Found - Gun barrel at corner. Also Haines "T" Iron, not recorded.  
8" Fir N.80°W., 22.3 ft., now stump, checks for bearing and distance.  
6" Fir N.84°W., 5.3 ft., no trace.  
15" Yew N.14°W., 20.7 ft., mkd. "¼ S17 BT" by Haines, not recorded.  
Scribed -23" Maple N.32°E., 22.0 ft. mkd. "¼ S16 CS BT".  
Corner is in fence corner, N and W.