

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1342)

Set post cor. of secs. 8, 9, 16 and 17, from which
A Fir 6" dia., bears N.41°W., 29 lks. dist.
A Fir 12" dia., bears N.23°E., 27 lks. dist.
A Fir 8" dia., bears S.35°E., 24 lks. dist.
A Cedar 10" dia., bears S.20°W., 10 lks. dist.

Present: Bert Stock; A.E. Jones; A.J. Lee; Cutlack Bros. -
Jan. 10, 1900 - Vol. 2 Page 261

Set a Yew post, from which
A W. Fir 30" dia., bears N.17°E., 42 lks. dist.
The SW BT is standing with 2 blazes, but no marks, which probably were cut out.
Two other BTs were lying down, but plainly marked, so I remark the old original SW BT.
No other trees within limits.

Kenneth P. McReynolds, LS #277 - Feb. 1955 - C.S. File 41/340

Drove an iron rod 5/8" x 30".
Only one BT remained, a Cedar stub.
I established 3 additional BTs as follow:
Cedar 8" dia., bears N.58°W., 32.8 ft.
Maple 22" dia., bears N.57°30'E., 71.0 ft.
Maple 24" dia., which bears S.72°20'E., 72.0 ft.

Wilford Haines - C.S. File 49/42-67 (1) (Date ?)

Found section scribed on:
12" Cedar N.60°W., 32.8 ft. (rescribed)
24" Maple N.57½°E., 71.0 ft.
32" Maple S.72°E., 72.0 ft.
Original SW BT (stub) scribe still visible.

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #516 - Surveyed July 29/Aug. 23, 1963 - (DCSO records Vol. 32 Page(s) 13428)

The Sec. cor., perpetuated by Wilford Haines, with a 1" T-Iron, firmly set, protruding 8" above ground, with alum. cap marked "Wilford N. Haines, No. 239, Drain, Oregon, at record bearing and distance from the original SW bearing tree:
(Cont. Next Page)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Cedar snag 35" dia., bears S.20°W., 10 lks. dist. mkd. 22 S on open blaze.
and trees mkd. by the Douglas County Surveyor:
A Maple 30" dia., bears N.57½°E., 110 lks. dist. mkd. with a healed blaze.
A Maple 38" dia., bears S.70°E., 108 lks. dist. mkd. with a healed blaze.
A Cedar snag 14" dia., bears N.60°W., 47 lks. dist. mkd. T22S R4W S8 BT.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:
T 22 S R 4 W
S 8 | S 9
S 17 | S 16
1963

from which new bearing trees
A Cedar 22" dia., bears S.4°W., 155 lks. dist. mkd. T22S R4W S17 BT.
A Cedar 7" dia., bears N.35½°W., 53 lks. dist. mkd. T22S R4W S8 BT.
Reset the T-iron alongside the iron post.

Fd. OK, Sept. 1992 by D. Peel - M 115-77

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO recs Vol. 55 Pgs 21811-2)

The cor. of secs. 8, 9, 16, & 17, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree
A cedar snag, 35" dia., bears S.20°W., 6.6 ft., no marks visible on an opened, decayed blaze.
and the remains of BTs mkd. by McReynolds, in 1955 (record, incorrectly attributed to the Douglas County Surveyor by Beck)

A maple, 34" dia., bears N.57½°E., 72.6 ft., with a healed blaze.

A maple, 44" dia., bears S.70°E., 71.3 ft., with a healed blaze.

A cedar snag, 14" dia., bears N.58¼°W., 34.2 ft., no marks visible on a partially healed blaze. (Record, N.60°W., 31.0 ft.)

and the remains of a bearing tree mkd. by Beck
A decayed cedar stump, 35" dia., bears S.4°W., 102.3 ft., no marks visible on an opened, decayed blaze.

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

and new bearing trees

A cedar, 5" dia., bears S.59¼°W., 28.4 ft., mkd. X BT.

A cedar, 18" dia., bears N.47¼°W., 34.9 ft., mkd. T22S R4W
S8 BT.