

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 300640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 4 and 5

|             |                   |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #514, dated August 27, 1884 (DCSO records Vol. 4 Page(s) 1365)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in the ground for qr. sec. cor., marked ¼ S on W. face, from which  
A Fir 30" dia., bears S.89°E., 81 lks. dist. mkd. ¼ S BT  
A Fir 36" dia., bears N.50°E., 15 lks. dist. mkd. ¼ S BT

Douglas Co. Surveyors Office - Bruce Rogers, Deputy, Stone and Stoffel, crew - Jan. 26, 1965 - C.S. File 53/101-83

-----  
Found 4" x 4" Cedar post but no trace of BTs. Original notes call for stone. There is a Weyerhaeuser tag and Haines tag by this post but no recorded renewal by these people.

Survey by Burton Holt - For: Sun Studs - Feb. 1981 - C.S. File 58/252(n) and M 86-56

-----  
(Witness Corner for ¼ corner)  
Set 1½" x 36" I.P. with brass cap for Witness Corner. 1/4 Corner bears 3.18 ft. South.  
BTs - 14" D.Fir bears N.72°30'E., 9.0 ft. scribed WC ¼ S4 BT  
7" D.Fir bears S.62°W., 24.1 ft. scribed WC ¼ S5 BT.

Found OK by N. Hibbs, Dec. 2000 - M132-57