

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; and 4, T23-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by - James E Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Pgs 2267 & 2270)

Set ¼ sec. post, from which
A Laurel 12" dia., bears S.38°E., 16 lks. dist.
A Fir 8" dia., bears N.18°W., 60 lks. dist.

Floyd Cole, Deputy - Wit: C.F. Andrew and O.A. Parker - April 5, 1915 - Vol. 2 Pages 202-4; Field Book 40 Page 14 (and "old" corner book Vol. 1 Page 17)

Renew corner with Vine Maple stake from orig trees still standing.

Survey by Glen McChesney - (Under Lester E. Calder) - For: Weyerhaeuser Co. - June 1960 - C.S. 51/87-3 & C.S. 53/105-39

GLO survey record, post, no trace.
Found - 12" Laurel S.38°E., 10.6 ft., 18" Laurel, down, rotted and hollow, but scribing visible.
8" Fir N.18°W., 39.6 ft., 28" Fir, scribing visible.
1" Iron rod for corner, good for dist. & brg. from GLO BTs.
Referenced by McChesney (Plates and "W" nails only)
28" Fir N.17°W., 38.2 ft., orig. BT.
44" Fir S.5°W., 45.6 ft.

Wilford N Haines - Date ? filed 12/1965 - C.S. File 54/16-23F - Added 3/13/218

Found - 26" Fir, N.16°W., 39.5 ft. (standing) W.T. Co. spike in butt.
12" Laurel, S.38°E., 16 lks (gone)
Scribed- 48" Fir S.06°W., 48.3 ft. W.T. Co. Spike in butt.

Survey by Robert G. Dean - For: Don Jackson - May 12, 1980 - C.S. File 58/204(N) and M 83-37

Found - 1" Iron rod.
31" Fir snag "¼S" visible, N.18°08'W., 39.3 ft. (Orig. BT, N.18°W., 39.6 ft.)
44" Fir windfall, S.3°W., 50.4 ft. approx.
Haines T Iron South, 0.1 ft.
New BTs - 8" W.Fir scribed "BT" at base N.30°W., 15.3 ft.
8" W.Fir S.34°37'E., 18.7 ft. scribed "BT" at base.

Fd. Ok by Les Roberts, 6/96 M 125-29