

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor for Sec 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Floyd Cole, Deputy with Norris and Letsom, crew - March 2, 1915 - Vol. 2 Page 203

Found by crossing true ¼ lines.

Set corner and mark:

A W.Oak 9" N.3½°E., 778 lks.

A Maple 24" S.65°E., 249 lks.

An Ash 14" N.15°W., 923 lks.

A W.Oak 7" S.23°35'W., 469 lks.

Survey by Glen McChesney under Lester E. Calder - For: Weyerhaeuser Co - June 1960 - C.S. 51/87-3 & c.s. 53/105-23*

Found - 9" Oak N.3½°E., 513.5 ft., gone.

24" Maple S.65°E., 164.3 ft., gone.

14" Ash N.15°W., 609.2 ft., 20", 2 faces healed over

7" Oak S.23°35'W., 309.5 ft. - 24", scribing visible

Drove a Weyerhaeuser Co. "W" nail into paved Co. Rd. by dist. from NW. and SW. CS BTs.

Referenced by G. McChesney*:

3/4" Iron rod, N.4°E., 34.0 ft. CR R/W P.O.T. 110+50

3/4" Iron rod S.7½°E., 26.5 ft. CR R/W P.O.T. 110+50

10" Power pole N.20°E., 36.5 ft. plated and "W" nails only.

Survey by Robert Dean - For: Don Jackson - May 12, 1980 - C.S. File 58/204(n) and M 83-37

Found - 3/4" Iron rod bears S.1°26'E., 27.14 ft.

3/4" Iron rod bears N.1°23'E., 32.67 ft.

23" double W.Oak, hollow scar, bears S.23°30'W., 311.3 ft. (Rec. S.23°35'W., 303.6 ft.)

27" Ash, good scars bears N.15°06'W., 609.3 ft. (Rec. N.15°W., 609.2 ft.)

Set a square 1/2" iron spike in pavement from which:

A 1/2" Iron rod bears S.0°05'10"W., 27.13 ft.

David Wellman - For: Donald- July 2005 - M148-20

Two separate pts for the center ¼ sec cor of sec. 33 were fd to exist during this survey. In 1915, F. Cole, Douglas. Co. Deputy Surveyor, established the center 1/4 corner as recorded in Douglas County Survey Vol 2, pg 203, & was subsequently perpetuated by G McChesney, WEYCO, in 1960, as recorded in M2-59. A second center ¼ cor. position was established by R. Dean, in 1980, as recorded in Douglas Co survey M83-37. The calculated bearing & distance between these two points is shown in this survey. cont. next pg

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A conflict exists as there are two identified center ¼ sec. corner recorded positions, with subsequent differences in location of the north/south centerline of section 33. As this survey was to establish and locate an easement in the southwest quarter of the section, the client did not choose to rectify any found discrepancies along the north/south centerline.