

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1340)

Set qr. sec. post, from which
An Ash 10" dia., bears S.77°W., 52 lks. dist.
An Alder 18" dia., bears N.3°E., 17 lks. dist.

Floyd Cole, Deputy - Wit: C.F. Andrew; O.A. Parker - April 5, 1915 - Vol. 2 Pages 202-4 and Field Book 40 Paage 14 (and "old" corner book Vol. 1 Pg 17)

Renew corner, marked new trees.
An Oak 12" dia., bears S.39½°W., 43 lks.
An Oak 18" dia., bears N.46°E., 122 lks.

Douglas Co. Surveyors Office - Wm. S. Stoffel; Mike Stone, crew - Dec. 1964 - C.S. File 53/101-64

Found - 12" W.Oak S.39½°W., 43 lks., opened and found scribing "¼ S CS". (now 24")
18" now 24" W.Oak N.46°E., 122 lks., good scar.
Corner falls in creek, therefore Set WITNESS CORNER.
Set Brass cap mkd: County Surveyors Office
T 22 S R 4 W
WC ¼ S 28
S33
Corner 40' West
New BTs -18" W.Oak N.57°E., 52.0 ft. mkd. WC ¼ S28 CS BT.
20" W.Oak S.45°W., 50.6 ft. mkd. WC ¼ S33 CS BT.

Fd. OK, Feb. 1991 - M 111-66