

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Steven P. Ness, L.S. #811, For: Weyerhaeuser Company - March 30, 1993 - M 116-66

Set - 2½" Brass cap on 2" x 40" Iron pipe marked: T22S R4W C¼ S21 "1993 RPLS 811".

BTs - 8" D.Fir N.45½°E., 32.4 ft. to center, 32.05 ft. to "W" nail, scribed "BT" on low face, blaze "X" chest high.

4" D.Fir N.2°W., 24.9 ft. to center, 24.79 ft. to "W" nail, scribed "BT" on low face, blaze "X" chest high.

No accessories available to the South.

Found OK by D. Baker, Mar. 2002 - M137-51

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO recs Vol. 55 Page 21818)

The center 1/4 sec. cor. of sec 21, established by Ness, in 1993, and is accepted as the cor., monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Ness

A fir, 9" dia., bears N.0¼°E., 25.1 ft., with a healed double blaze.

A fir, 12" dia., bears N.45¼°E., 32.8 ft., with a healed double blaze.