

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCS0 records Vol. 3 Page(s) 1343)

-----  
Set ¼ sec. post, from which  
    A Fir 30" dia., bears N.32°W., 29 lks. dist.  
    A Fir 18" dia., bears S.4°E., 50 lks. dist.

Kenneth P. McReynolds, LS #277 -C.L. Spaulding property - Feb. 23, 1955 - C.S. File 41/340 and M 9-50

-----  
(Per legend on map)  
Iron pipe set and BT scribed. Exterior corners

Douglas county Surveyors Office - James W. Byron - May 12, 1958 - C.S. File 49/59-24

-----  
Found - ½" I.P. set by McReynolds.  
    I do not find his BT, nor can we find either orig. BT.  
    The tree use by McReynolds is now 60" Fir, record 30"; it shows real old axe marks. I open old scar, but do not find scribe.

Milo E. Godfrey, Douglas Co. Surveyors Office - July 8, 1963  
C.S. File 49/59-39

-----  
(Visited this corner per request of Ed Ware, dated June 4, 1963. Mr. Ware found Haines T-Iron in good condition and 44" D.Fir S.32°E 19 ft., orig. and down.)

Found - Haines T Iron and cap driven alongside ½" Iron pipe.  
    Fir tree, now 48" dia., recent blowdown, bears N.32°W., 19 ft. Bark scribing on Fir "¼ S9 BT 363", also cruiser's marks. Some fairly old. Had been cut open 5 to 10 years ago to an old injury. No evidence of scribing and no old axe marks. No evidence visible that this was original BT.  
No new BTs found. No record of renewal.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Mike Stone, J. Layne, crew - Feb. 7, 1966 - C.S. File 53/101-46

-----  
Found - ½" I.P. and Haines "T" Iron as found and recorded by Godfrey, 1963.  
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

"363" bark scribed on 48" Fir N.32°W., 19.0 ft. This tree was recorded in Martin's Field book #2 Pg. 6 as orig. & rebark scribed by him. Also Martin mkd. a new BT as follows:  
7" now 9" Fir S.69°W., 9.0 ft. now down & pushed out of place, Haines' button on partially healed face  
No trace of orig. SE. BT.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 22 S R 4 W  
S 9  
S 16  
1966  
New BTs -4" W.Fir N.1°E., 120.7 ft. mkd. ¼ S9 CS BT.  
12" Cedar S.12°E., 53.7 ft. mkd. ¼ S16 CS BT.  
This corner lies approx. 100 ft. South of ridge, course E-W.

Fd. OK, Aug. 1994 by K. Hoffine - M 121-9

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor and Robert H. Browning, Surveying Technician, under Group #1935, surveyed Jan./Feb. 2000 - (DCSO rec. Vol. 53 Page(s) 20375-6)  
-----  
The ¼ sec. cor. of secs. 9 & 16, perpetuated by McReynolds, in 1955, further perpetuated by Tracy, in 1966, monumented with an iron post, 1¼" diam., firmly set, projecting 6" above ground, (along the East side of which is an iron pipe, ½" diam., firmly set, projecting 18" above ground), with properly marked brass cap,  
from which the remains of an original bearing tree  
A sawed & decayed fir stump, 48" diam., bears N.32°W., 19.1 ft., with no marks visible.  
and the remains of bearing trees mkd. by Tracy  
A fir, 20" diam., bears N.1°E., 120.3 ft., with a healed double blaze.  
A sawed cedar stump, 26" diam., bears S.12 ¾°E., 54.1 ft., with a healed double blaze.  
and a new bearing tree  
A fir, 17" diam., bears S.¾°W., 51.9 ft., mkd. ¼ S16 BT.  
Corner is located 10.0 ft. N. of a dirt skid road, 10 ft. wide, bears East and West.  
Each new bearing tree has a 2½" X ¼" magnetic nail (Mag Nail) driven at the base on right side-center

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO records Vol. 55 Pg 21811)  
-----

continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The ¼ sec. cor. of secs. 9 & 16, monumented with an iron post, 1¼" dia., firmly set, projecting 6" above ground (alongside of which is an iron pipe, 1/2" dia., firmly set, projecting 18" above ground), with brass cap mkd. from which the remains of an original bearing tree

A sawed, decayed fir stump, 48" dia., bears N.32°W., 19.1 ft., no marks visible.

and the remains of BTs mkd. by Tracy, in 1966, reported by Skeesick and Browning

A fir, 22" dia., bears N.1°E., 120.3 ft., with a healed double blaze.

A root hole bears S.12¾°E., 54.1 ft., with sawed, burnt cedar stump, size indeterminate, lying alongside, no marks visible.

and a bearing tree mkd. by Skeesick and Browning

A fir, 22" dia., bears S.0¾°W., 51.9 ft., with a healed blaze.

The geographic position (NAD 1983 (CORS 96)) of the following corners, as determined in a least squares adjusted network of conventional survey control and GPS occupied points, utilizing dual frequency carrier phase GPS receivers, relative to National Spatial Reference System (NSRS) Continuously Operating Reference Stations (CORS) "DCSO CORS ARP" and "OBEC CONS COOP CORS ARP", is as follows.

Latitude: 43°39'49.39"N. Longitude: 123°10'37.53"W.