

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 4; and 33 of T21-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 2 Page(s) 752)

Set ¼ sec. post, from which
A Fir 10" dia., bears S.5½°W., 18 lks. dist.
A Fir 8" dia., bears N.10°W., 6 lks. dist.

BLM resurvey by James E. Jelley and Wayne L. Rogers, under Group #1026, surveyed July 15, 1980/March 12, 1981 (DCSO records Vol. 44 Page(s) 16955-56)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 21 S R 4 W
1/4 $\frac{S \ 33}{S \ 4}$
T 22 S R 4 W
1980

from which
A Fir 10" dia., bears S.51½°W., 74 lks. dist. mkd. ¼ S4 BT
A Fir 12" dia., bears N.45½°W., 46 lks. dist. mkd. ¼ S33 BT.

David Wellman - For: Summerwood Inc. - June 1999 - M 132-12

Found - USBLM brass cap dated 1980, 0.1 ft above ground.
12" Fir N.43°W., 31.6 ft. to spike set side center - closed face - rec: N.45½°W., 46 lks. 1980 BLM
16" Fir, S.54°W., 30.8 ft. to spike set side center - closed face - rec: S.51½°W., 74 lks., 1980 BLM
Set - 20" Fir, N.89½°E., 13.7 ft. to spike set side center scribed "T21S ¼ S33 BT."
28" Fir S.6½°E., 14.8 ft. to spike set side center scribed "T22S ¼ S4 BT"