

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; and 3 & 4, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - James E. Freeman Deputy Surveyor, under Contract #1, dated May, 28, 1851 (DCSO records Vol. 6 Page(s) 2266 and page 2269)

Set post cor. to secs. 3, 4, 33 and 34, from which
A Fir 36" dia., bears N.50°W., 12 lks. dist.
A Fir 18" dia., bears S.35°E., 15 lks. dist.
A Fir 18" dia., bears N.40°E., 38 lks. dist.
A Fir 16" dia., bears S.27½°W., 11 lks. dist.

Floyd Cole, Deputy - Wit: C.F. Andrew and O.A. Parker - April 5, 1915 - Vol. 2 Pages 202-4; Field Book 40 Pg. 14 (and "old" corner book, Vol. 1 Pg 17)

Tree in Sec. 34 standing. Others down.
Remark - A Cedar 16" dia., S.51°15'W., 19 lks.
A Fir 18" dia., N.25°50'W., 55 lks.
A double Maple 14" dia., S.75°45'E., 55 lks.

Survey by Wilford N. Haines - For: E.G. Whipple Mill - June 1961 - M 22-6 (& C.S. File 54/16-23R)

Found - Scribed stake and 1" Iron pipe.
NE BT is a rotten stub.
Set 1" x 1" x 36" "T" Iron by pipe and scribed:
12" I.Cedar N.16°W., 25.5 ft.
10" I.Cedar S.80°E., 28.0 ft.

BLM Resurvey by C. Albert White and Donald R. Beck, Cadastral Surveyors, under Group # 243 and 350, Surveyed April/June 1963 - (DCSO records Vol. 32 Page(s) 13269)

The Sec. Cor., perpetuated by Haines in 1961, with an iron pipe, 3/4" dia., protruding 10" above ground, and with a 3/4" "T" iron, protruding 8" above the ground, with a brass disc 3/4" dia., on top, mkd. "Wilford N. Haines Drain Ore. 239 Survey Point", from which the remains of the original bearing trees:

A rotted Fir stump 25" dia., bears N.40°E., 38 lks. dist. with no marks remaining.
A Fir stump hole, bears N.50°W., 12 lks. dist. and trees mkd. by Haines:
A Cedar 15" dia., bears N.89°E., 39 lks. dist. mkd. T22S R4W S34 BT, on open blaze.
A Cedar 17" dia., bears N.14½°W., 47 lks. dist. mkd. T22S R4W S33 BT, on open blaze.
and a tree mkd. by persons unknown:
(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 33 & 34; and 3 & 4, T23-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar 25" dia., bears S.66 3/4°W., 20 lks. dist. mkd. with partial scribe marks on nearly healed blaze, and mkd. 363 in the bar, by Haines.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 22 S R 4 W

S 33 | S 34

S 4 | S 3

T 23 S

from which new bearing trees

A Maple 17" dia., bears S.11°E., 94 lks. dist. mkd. T23S R4W S3 BT.

A Fir 8" dia., bears S.9°W., 45 lks. dist. mkd. T23S R4W S4 BT.

Deposit local corner material beside the iron post.

Fd. June 1990 - M 110-39

Harvey Christensen - For: Seneca Jones Timber Co. - Dec. 1999 - M 134-4

Found - 1963 2.5" BLM BC, .8 ft. above grade
Haines T post 0.8 ft. above ground alongside.
31" I.Cedar N.17°W., 30.1 ft., healed face.
29" I.Cedar S.88°E., 26.2 ft., healed face.

New BOs- 10" D.Fir, S.25°W., 22.0 ft., blazed & scribed "T23S R4W S4 BT"
5' steel post 1 foot west.

Fd. & used on BLM Dependent resurvey by Timothy J. Moore, Cadastral Surveyor and Robert H. Browning, Surveying Technician under Group #1955, surveyed 2000/2001. (DCSO rec. Vol. 54 page(s) 20831-2)