

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 28

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1337)

Set ¼ sec. post, from which
 A Fir 36" dia., bears S.18°W., 31 lks. dist.
 A Fir 18" dia., bears N.33°E., 27 lks. dist.

C.C. Boyer - Mar. 11, 1915 - F.B. 40 Pg. 20

Find original marks on tree S.18°W. Remark same.
Fir 40", N.19°W., 22 lks.

Wilford N. Haines - Feb. 1957 - M 4-51

Found - SW BT down.
 48" Fir N.19°W., 22 lks.
Set a 36" T Iron with brass cap inscribed "Survey Point-
Wilford N. Haines #239".

Fd. OK, Feb. 1991 - M 111-66

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO recs Vol 55 Pgs 21795-6)

The ¼ sec. cor. of secs. 27 & 28, perpetuated by Boyer in 1915; subsequently perpetuated by Haines, in 1957, monumented with an iron T-post, 1" sq., firmly set, projecting 8" above ground, with brass disk mkd. WILFORD N HAINES 239 SURVEY POINT DRAIN ORE, from which the remains of an original BT

 A root hole bears S.33¾°W., 26.3 ft., with a fallen decayed fir, size indeterminate, lying alongside, no marks visible. (Record, S.18°W., 20.5 ft.)
and the remains of a bearing tree mkd. by Boyer
 A sawed fir stump, 53" dia., bears N.14½°W., 14.8 ft., no marks visible.

At the cor. point

Set a stainless steel post, 28" long, 2½" dia., 25" in the ground, directly over the T-post, with brass cap mkd.

T22S R4W

¼

S28|S27

2007

from which new bearing trees

 A fir, 6" dia., bears S.2¼°E., 15.2 ft., mkd. ¼ S27 BT.

 A fir, 9" dia., bears N.60°W., 34.2 ft., mkd. ¼ S28 BT.