

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1337)	

Set post cor. of secs. 21, 22, 27 and 28, from which A Fir 8" dia., bears N.48°W., 23 lks. dist. A Fir 10" dia., bears S.66°E., 8 lks. dist. An Alder 12" dia., bears S.80°W., 18 lks. dist. A Cedar 8" dia., bears N.31°E., 52 lks. dist.	
Wilford N. Haines - Feb. 1957 - M 4-51 and Haines Envelope 6 (H. en 6)	

Found steel rod on SE. side of small creek at end of fence. Old BTs have been destroyed by logging operations years ago. Mr. Sehlin says this rod within a foot of original. Distance South to ¼ corner checks with Cole's survey of 1915. Set a 48" T Iron with brass cap inscribed "Survey Point-Wilford N. Haines #239". From which 26" Fir S.88°E., 105.8 ft. 52" Fir N.31°W., 62.7 ft.	
Fd. OK, Feb. 1991 - M 111-66	
Bruce Shaner - July 23, 1997 - M 127-26 & C.S. 65/15-8C	

Mon. FD.-	Haines T Iron on south bank of small stream
Bt's Fd.-	Cedar End post (of fence that runs north), bears North 19'. 36" D.Fir (rec. 26"), bark scribes visible, bears N.88½°E. (rec. S.88°E), 95.5' (rec. 105.8' was probably slope dist.). 72" D.Fir (rec. 52"), bark scribes visible, bears N.31°W., 53.4' (rec. 62.7' was probable slope dist.)
Mon. SET-	Old tags & Haines brass washers on both trees. ¾" Aluminum Cap on a 2½"x30" Alum. Pipe, cap marked SHANER ENGR T22S R4W <u>S21 S22</u> S28 S27 RLS 430 1997
New Accessories - 14" D.Fir BT, I scribed "T22S R4W S27, BT", bears S.14°E., 16.2'. 8" D.Fir Bt, I scribed "T22S R4W S28, BT", bears S.87°W., 26.6'. I reset Haines T Iron alongside Alum. pipe.	

PRIMARY CORNER DESCRIPTION Sec. Cor. for 21, 22, 27 and 28

Alias	Description

Found OK by B. Shaner, Sept. 2001 - M137-19 & CS65/37-21A

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21797-8)

The cor. of secs. 21, 22, 27, & 28, perpetuated by person(s) unknown, subsequently perpetuated by Haines, in 1957, further perpetuated by Shaner, in 1997. This position is harmoniously related with identified existing original cors. in the area, has long been recognized by owners of the adjacent lands as the cor., and is accepted as the best available evidence of the original cor. position, monumented with an aluminum post, 2½" dia., firmly set, projecting 8" above ground, with aluminum cap (properly) mkd.

from which bearing trees mkd. by Haines

- A fir, 38" dia., bears N.88½°E., 97.5 ft., with fragmentary scribe marks visible on the bark.
- A fir, 72" dia., bears N.30°W., 54.7 ft., no marks visible.

and bearing trees mkd. by Shaner

- A fir, 17" dia., bears S.16°E., 15.6 ft., with a healed blaze.
- A fir, 9" dia., bears S.85°W., 26.2 ft., with a healed blaze.

and a reference monument

- An iron rod, 30" long, 5/8" dia., driven 28" in the ground, for a reference monument, bears S.70°10'E., 12.3 ft., with aluminum cap mkd. RM T22S R4W S27 12.3 FT TO COR 2007 and an arrow pointing toward the cor.