

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1337)

Set ¼ sec. post, from which
A Fir 36" dia., bears N.73°W., 51 lks. dist.
A Fir 36" dia., bears N.34°E., 69 lks. dist.

Wilford N. Haines - For: E.G. Whipple - (date ?) Filed Sept. 13, 1990 - H. En. 6 (Haines Envelope 6)

1" Iron pipe.
Fir 36" N.73°W., 51 lks., found.
Fir 36" N.34°E., 69 lks., found.

Wilford Haines - C.S. File 49/42-67(4) (Date ?)

Found East BT and rebark scribed.
Scribed:
12" Fir N.60°E., 6.0 ft.
10" Fir S.85°W., 6.3 ft.

Survey by Lester E Calder by Robert Barta - For: Weyerhaeuser Co. - Sept. 1962 - C.S. 51/87-6 & C.S. 53/105-18*

GL0 survey record post gone.
Found - Haines "T" Iron stake and ½" Iron pipe.
36" Fir N.34°E., 69 lks. now 42" Fir, bark scribing visible.
36" Fir N.73°W., 51 lks., now badly rotted and burned remains.
Referenced by R. Barta* (Plates and "W" nails only)
18" Fir N.59°E., 5.3 ft. (12" Fir N.60°E., 6.0 ft., Haines BT)
20" Fir S.34°W., 33.3 ft. (10" Fir S.85°W., 6.3 ft. Haines BT)

Fd. OK, March 1993 by Ness - M 116-66
Found OK by B. Shaner, Sept. 2001 - M137-19 & CS65/37-21C

BLM Dependent resurvey by A Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug 2007/Feb 2008 - (DCSO recs Vol. 55 Pg 21800)

The ¼ sec. cor. of secs. 21 & 22, perpetuated by Haines, date unknown, subsequently perpetuated by Calder, in 1962, monumented with an iron T-post, 1" sq. firmly set,
continued next page

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

projecting 5" above ground (alongside of which is an iron pipe, 17" long, 1" dia., firmly set, projecting 1" above ground), with brass disk mkd. WILFORD N HAINES 239 SURVEY DRAIN ORE, from which the remains of the orig. bearing trees

A decayed fir stump, 53" dia., bears N.34°E., 45.5 ft., no marks visible.

A decayed fir stump, size indeterminate, bears N.73°W., 33.7 ft., no marks visible.

and bearing trees mkd. by Haines

A fir, 21" dia., bears N.62°E., 6.2 ft., with scribe marks 4 S22 BT visible on the bark.

A fir, 19" dia., bears S.86°W., 6.2 ft., with a healed blaze.

and a reference by Calder

A fir snag, 26" dia., bears S.35°W., 34.8 ft., no marks visible.

At the cor. point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over the T-post, with brass cap mkd.

T22S R4W

¼

S21|S22

2007

Place the iron pipe inside the stainless steel post.