

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Harvey Gordon and Charles T. Gardner, Deputy Surveyors, under Contract #52 dated Feb. 17, 1855 (DCSO records Vol. 3 Page(s) 1337)

-----  
Set post, cor. of secs. 15, 16, 21 and 22, from which  
A Fir 40" dia., bears N.72°W., 202 lks. dist.  
A Fir 10" dia., bears S.28°E., 118 lks. dist.  
An Oak 8" dia., bears S.40°W., 137 lks. dist.  
A Laurel 10" dia., bears N.23°E., 114 lks. dist.

Wilford N. Haines - For: Whipple - (No date) - Filed Sept. 13, 1990 - H. En. 6 (Haines envelope 6)

-----  
1" Iron pipe. (Describes all four original BTs)

Survey by Lester Calder by Robert Barta - For: Weyerhaeuser Co. Sept. 1962 - C.S. File 51/87-6 & C.S. 53/105-21\*

-----  
GL0 survey record post gone, replaced by Haines "T" iron.  
Found - 10" Laurel N.23°E., 114 lks., all evidence gone.  
10" Fir S.28°E., 118 lks., now 44" Fir, chopped out, scribing visible.  
8" Oak S.40°W., 127 lks.; all evidence gone.  
40" Fir N.72°W., 202 lks., now 54" Fir.  
Referenced by Wm. L. Wilt\* (Plates and "W" nails only)  
28" Fir N.31°E., 37.7 ft.  
44" Fir S.28°E., 76.3 ft., orig. BT.  
12" Fir S.12°W., 14.7 ft.  
54" Fir N.72°W., 133.4 ft., orig. BT.

Douglas County Surveyors Office - Wm. S. Stoffel and Mike Stone, crew - Dec. 14, 1964 - C.S. File 53/101-53

-----  
Found - Haines T-Iron and 3/4" I.Pipe at corner.  
44" Fir S.28°E., 76.3 ft. scribing visible. Orig. BT  
54" Fir N.72°W., 133.4 ft. Orig. BT, remarked.  
28" Fir N.31°E., 37.7 ft., pushed out by loggers.  
12" Fir S.12°W., 14.7 ft., pushed out by loggers.  
New BTs - 8" Fir S.15°W., 128.6 ft. "T22S R4W S21 CS BT"  
13" Fir N.84°E., 64.0 ft. mkd. "T22S R4W S15 CS BT"

Wilford N. Haines - For: Whipple Logging Co. - June 1975 - H. En. 7 (Haines envelope 7) and Haines F.B. H-111 (Filed Sept. 13, 1990)

-----  
Found T-Iron and Weyerhaeuser post. SE BT still standing.

(Cont. Next Page)

TOWNSHIP 22 RANGE 04 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

BLM resurvey by Wayne L. Rogers, Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1415, Surveyed Jan. 7/March 29, 1988 - (DCSO records Vol. 48 Page(s) 18623)

-----  
The Sec. cor., perpetuated by Wilford Haines, date unknown, further perpetuated and recorded by Stoffel, DCSO in 1964, monumented with a "T" shaped iron rod 1" dia., firmly set, projecting 10" above ground, with washer mkd. "Wilford N. Haines Drain OR 239" alongside of which is an iron pipe, 3/4" dia., firmly set, projecting 5" above ground, from which the remains of an original bearing tree:

A burned Fir stump, size indeterminate, bears S.28°E., 117 lks. dist., no marks visible. (Rec. 118 lks.)  
and the remains of a bearing tree mkd. by Stoffel

A root hole, bears N.84°E., 97 lks. dist., with a down Fir stump alongside, size indeterminate, no marks visible.

At the corner point

Set an stainless steel post, 28" long, 2 1/2" dia., 24" in the ground, directly over the T iron, with brass cap mkd:

T 22 S R 4 W			
S 16		S 15	
S 21		S 22	
1988			

from which new bearing trees

A Fir 9" dia., bears N.69½°E., 19 lks. mkd T22S R4W S15 BT

A Fir 4" dia., bears S.25½°E., 31 lks. mkd. X BT.

A Fir 6" dia. bears S.59½°W., 54 lks. mkd. T22S R4W S21 BT

A Fir 5" dia., bears N.81½°W., 44 lks. mkd. X BT.

Deposit white "DEEP-1" magnetic marker at base and iron pipe alongside of stainless steel post.

From this point, the Douglas County Surveyors Office horizontal control station "EVE 1978", bears S.44°28'52"W., 317.260 chs., monumented with a brass tablet 3½" dia., concreted in bedrock, with top mkd. DOUGLAS COUNTY SURVEYORS OFFICE EVE 1978.

Fd. OK, March 1993 by Ness - M 116-66

BLM Dependent resurvey by A. Bert Skeesick Cadastral Surveyor, and Robert H. Browning, Surveying Tech. Group No. 2170 surveyed Aug. 2007/Feb. 2008 - (DCSO records Vol. 55 Page(s) 21802)

-----  
The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

continued next page

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A hollowed, decayed, burnt fir stump, size indeterminate, bears S.28°E., 77.9 ft., no marks visible.  
and the remains of a BT mkd. by Stoffel, in 1964, reported by Rogers and Moore  
A root hole, bears N.84°E., 64.0 ft., with decayed fir stump, size indeterminate, lying alongside, no marks visible.  
and bearing trees mkd. by Rogers and Moore  
A fir, 14" dia., bears N.69½°E., 12.5 ft., with a healed blaze.  
A fir, 7" dia., bears S.25½°E., 20.5 ft., with a healed double blaze.  
A fir, 14" dia., bears S.59½°W., 35.6 ft., with a healed double blaze.  
A fir, 11" dia., bears N.81½°W., 29.0 ft., with a healed double blaze.  
Corner is located on a shallow NW. slope.  
From the cor. N., 45 ft., a graveled road, 14 ft. wide, bears N.78°E. and S.78°W.

Adam DeGroot - For: Weyerhaeuser Co. - May 2020 - C.S. File 65/105-13

-----  
Found - A 2½" USBLM stainless steel post by Rogers in 1988, firmly set and projecting 5" above ground, with a ¾" brass cap properly marked.  
THE 1988 BTs -  
A 16" D.Fir bears N.69°30'E., 12.3 ft w/healed blaze (N.69°30'E., 19 lks)BLM 1988 (N.69°30'E., 12.5 FT) 2008 BLM  
A 7" D.Fir snag bears S.26°30'E., 19.9 ft w/healed blaze - I high stump (S.25°30'E., 31 lks)1988 BLM (S.25°30'E., 20.5 ft)2008 BLM  
A 17" D.Fir saw stump bears S.58°26'W., 34.96 ft to mag-hub & brass washer (S.59°30'W., 54 lks)1988 BLM (S.59°30'W., 35.6 ft)2008 BLM  
A 12" D.Fir N.82°30'W., 29.1 ft w/healed blaze (N.81°30'W., 44 lks)1988 BLM (N.81°30'W., 29.0 ft)2008 BLM  
New BTs-  
A 16" D.Fir saw stump bears S.55°32'E., 18.48 ft to MAG-HUB & brass washer  
A 12" D.Fir bears S.16°30'W., 45.9 ft scribed "T22SR4WS21BT" on dbl blaze